Peter Van Alyea Redwood Oil Company 455 Yolanda Avenue, Suite 200 Santa Rosa, CA 95404

Remediation System Operation Report Third Quarter 2005 Redwood Oil Company Bulk Plant 455 Yolanda Santa Rosa, CA

Dear Mr. Van Alyea:

ECM Group (ECM) has prepared this report summarizing the operation of the ground water remediation system at the above-referenced site (Figures 1 and 2, Appendix A). The system consists of a Ground Water Extraction (GWE) System and an Air Sparge (AS) System. A plan view of the system is shown on Figure 3 (Appendix A). A Soil Vapor Extraction (SVE) System was formerly operated at the facility. Operation of the SVE System was discontinued in September 2003.

### **System Operation**

A summary report describing system installation was submitted in November 2001. The GWE system was operational in June, 2001. The AS system was operational in July, 2001. The SVE system was initially activated on July 27, 2001. On August 22, 2001, the SVE system was deactivated in order to clean the furnace catalyst and bring the system to Bay Area Air Quality Management (BAAQMD) standards. Modifications were completed and the system was permanently reactivated on September 18, 2001.

A System Evaluation Report dated August 27, 2003 recommended deactivation of the SVE system.<sup>2</sup> The SVE system was deactivated September 5, 2003. Historical operating data for the SVE system is presented in Tables 1 and 2, Appendix B.

ECM, 2001, Remedial System Installation, Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, CA, November 12, 2001, 5 pages and 4 appendices.

<sup>2 2003,</sup> ECM, Remedial System Evaluation and Monitoring Reduction Proposal, 455 Yolanda Ave., Santa Rosa, CA August 27, 2003, 10 pages and 3 attachments.

The remediation system consists of nine wells (GWE/SVE-1 through GWE/SVE-9) which are constructed as combined GWE/SVE wells, seven GWE wells (PMCS-1 through PMCS-6, and GWE-10), three SVE wells (SVE-11 through SVE-13), and 14 air injection (sparge) points. Schematics of GWE wells are shown in Figures 4 and 5 (Appendix A). Schematics of SVE wells are shown in Figures 6 and 7 (Appendix A). Schematics for combined GWE/SVE well-heads are shown in Figure 8 (Appendix A). Schematics of an AS injection point is shown in Figure 9 (Appendix A). Typical conduit trench details are shown in Figure 10 (Appendix A). Layout of the water, air and electrical systems in the treatment system pad are shown in Figures 11 through 13 (Appendix A).

Analytic laboratory reports for system effluent water samples collected during the third quarter of 2005 are included in Appendix C. Operation and maintenance field notes are presented in Appendix D.

### **GWE System Operation**

The GWE system extracts ground water from a total of 16 wells (Figure 3, Appendix A). Table 3 (Appendix B) provides flow totalizer readings for the GWE system. Between system start-up and October 5, 2005, a total of 4,545,919 gallons of ground water were extracted by the system. Flow rate for the system over the third quarter of 2005 varied from 0.0 to 3.88 gallons per minute (GPM). Table 4 (Appendix B) provides ground water influent analytical results for the system. Table 5 (Appendix B) provides measurements of ground water levels in extraction wells. Water levels in extraction wells are currently measured semi-annually. As a measure of system performance, water levels in extraction wells may be compared to water levels in site monitoring wells (Table 7, Appendix B). System extraction wells are approximately 30 ft in depth and contain pumps which are 5 ft in length. Pumps are set approximately 0.5 ft from the bottom of each well. A water level of approximately 24 to 30 ft bgs in an extraction well is an indicator of optimum performance. Water levels in extraction wells are provided in Table 5 (Appendix B).

### **Air Sparge System Operation**

The air sparge system consists of 14 air injection points (Figure 3, Appendix A). Table 6 (Appendix B) presents air flow readings for each sparge point since system start-up, which are now recorded quarterly. Air is delivered to the injection points at approximately 20 psi.

The AS system was designed to operate in conjunction with the SVE system. Operation of the AS system at its previous flow rate (2 to 10 scfm) without the SVE system in operation to

remove volatilized hydrocarbons is not advisable. Since deactivation of the SVE system, the AS system has been converted to a low-flow system, with a flow rate of less than 1 scfm for each injection point. The purpose of the low flow system is to continue to introduce oxygen into the subsurface, encouraging bioremediation.

On April 24, 2005 the air sparge portion of the remediation system was deactivated for an efficiency evaluation. The air sparge system remained off during the third quarter of 2005.

### SYSTEM PERFORMANCE EVALUATION

### **GWE System Performance Evaluation**

System performance may be measured by quantity of hydrocarbons removed. Since hydrocarbons have a very low solubility in water, mass of hydrocarbons removed by a ground water extraction system is typically low relative to the quantity of hydrocarbons sorbed to soil. Another measure of system performance is the system's ability to control the offsite migration of impacted ground water.

During the third quarter of 2005, a total of 301,529 gallons of ground water were extracted by the system (Table 3, Appendix A), at a flow rate of between 0.0 and 3.61 GPM. Hydrocarbon removal is calculated using the ground water influent hydrocarbon concentrations in Table 4 (Appendix B) and the figures for gallons discharged in Table 3 (Appendix A). Assuming the influent stream sample collected on July 7, 2005 was typical for the quarter as a whole (i.e., assuming an average concentration of 270 parts per billion (ppb) for gasoline, 350 ppb for diesel, and 360 ppb for MTBE), then mass of contaminant removed by the GWE system during the third quarter was approximately 0.71 kg of gasoline and diesel and 0.41 kg of MTBE. Quarterly hydrocarbon removal rates are shown in Table 8 and Graph 1 (Appendix B).

Water level measurements are now collected in pumping wells and monitoring wells on a semi-annual basis. Water level measurements in pumping wells and monitoring wells are used to evaluate GWE system performance in terms of drawdown and plume migration control. Figure 2 (Appendix A) shows inferred ground water elevation contours based on the measurements collected during January, 2005. Water levels for GWE wells were measured on April 22, 2005 to evaluate system performance. Measurements are provided in Table 5 (Appendix B).

### **AS System Performance Evaluation**

The most significant measurement of AS system performance is air flow through each wellhead. Air flow is currently 1 scfm or less in each injection point for a total of approximately 14 scfm. Table 6 (Appendix A) shows details of hours of operation and sparge point data.

Thank you for allowing ECM to provide environmental consulting services to Redwood Oil Company. Please call if you have questions or require additional information.

Sincerely, ECM Group

David Hazard Staff Scientist

Chris Bramer

Professional Engineer #C048846

Attachments: Appendix A - Figures

Appendix B - Tables

Appendix C - Laboratory Analytical Reports and Chain of Custody Record

Appendix D - Field Notes

cc: Joan Fleck, NCRWQCB

### APPENDIX A FIGURES




Figure 1. Site Location Map - Redwood Oil Service Station, 455 Yolanda Avenue, Santa Rosa, California





Figure 2. Monitoring Well Locations and Ground Water Elevation Contour Map - September 9, 2005 - Redwood Oil Bulk Plant, 455 Yolanda Avenue, Santa Rosa, California



## **Ground Water Extraction Well** air filter/regulator & gauge assembly 1" water discharge hose to ground water pump air feed line $\rightarrow$ : grout to surface slotted PVC well casing - 2' minimum bentonite plug (10' bgs) sand 20' of 0.020 slotted well casing - 10 -12" borehole 4" PVC well casing -Total depth 30'

Figure 4. Groundwater Extraction Well Diagram - Redwood Oil Bulk Plant - 455 Yolanda, Santa Rosa, California




Figure 5. Groundwater Extraction Well Head Detail - Redwood Oil Bulk Plant - 455 Yolanda, Santa Rosa, California

# **Soil Vapor Extraction Well** grout to surface slotted PVC well casing 2' minimum bentonite plug (5' bgs) sand 15' of 0.020 slotted well casing 10 -12" borehole 4" PVC well casing Total depth 20'

Figure 6. Soil Vapor Extraction Well Diagram - Redwood Oil Bulk Plant - 455 Yolanda, Santa Rosa, California




Figure 7. Soil Vapor Extraction Well Head Detail - Redwood Oil Bulk Plant - 455 Yolanda, Santa Rosa, California




Figure 8. Combined Ground Water and Soil Vapor Extraction Well Head Detail - Redwood Oil Bulk Plant - 455 Yolanda, Santa Rosa, California




Figure 9. □Air Injection Well Diagram - Redwood Oil Bulk Plant - 455 Yolanda, Santa Rosa, California





Figure 10. Pipe Trench Detail - Redwood Oil Bulk Plant - 455 Yolanda, Santa Rosa, California







REMEDIATION SYSTEM

Redwood Oil Bulk Plant, 455 Yolanda Avenue, Santa Rosa California WATER SYSTEM

PROJECT NUMBER	98-507-95	DRAWN BY	RG
ORIGINAL DATE		CHECKED BY	СВ
REVISION DATE	2/24/05	FIGURE NUMBER	11









REMEDIATION SYSTEM Redwood Oil Bulk Plant, 455 Yolanda Avenue, Santa Rosa California

ELECTRICAL SYSTEM

PROJECT NUMBER	98-507-95	DRAWN BY	RG
ORIGINAL DATE		CHECKED BY	СВ
REVISION DATE	2/10/05	FIGURE NUMBER	13

APPENDIX B
TABLES & GRAPHS

Table 1. Vapor Extraction System Flow Calculations - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Influent Concentration (ppm)	Influent Concentration μg/l²	Removal Rate Kg/day³	
7/27/01	327	1,360	11.7	
8/1/01	214	890	7.7	
8/2/011	200.23	834.2	7.2	
8/10/01	256	1,064	9.2	
8/20/01	224	931	8.0	
9/12/011	52.51	222.1	1.9	
9/25/01	102	424	3.6	
10/5/01	118	490	4.2	
10/16/01	242	1,006	8.7	
11/2/01	120	499	4.3	
11/9/01	97	403	3.5	
12/12/011	162.6	681	5.8	
3/12/02 4	2.6	10.8	0.1	
3/29/02 5	321	1,334	11.4	
4/5/02	5.2	21.6	0.2	
4/26/02	0	0	0	
5/16/02	4.3	17.9	0.2	
5/24/02	6.5	27.0	0.2	

Table 1. Vapor Extraction System Flow Calculations - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Influent Concentration (ppm)	Influent Concentration μg/l²	Removal Rate Kg/day <sup>3</sup>	
5/29/02	3.6	14.9	0.1	
6/7/02	4.3	17.9	0.2	
6/13/02	3.2	13.3	0.1	
6/28/02	2.3	9.6	0.1	
7/2/02	3.8	15.8	0.1	
7/19/02	148	615.2	5.2	
7/25/02	4.7	19.5	0.2	
8/1/02	205	852.2	7.2	
8/8/02	2.3	9.6	0.1	
8/14/02 1	121	504.4	4.3	
8/16/02	4.7	19.5	0.2	
9/9/02 6	29.9	124.3	1.1	
9/10/02	4.3	17.9	0.2	
9/16/02 7	58.6 / 9.9	243.6 / 41.2	2.1 / 0.35	
9/27/02 7	10 / 2.9	41.6 / 12.0	0.36 / 0.1	
10/2/02	1.8	7.5	0.1	
10/11/02	2.3	9.6	0.1	
10/18/02	2.2	9.1	0.1	

Table 1. Vapor Extraction System Flow Calculations - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Influent Concentration (ppm)	Influent Concentration μg/l²	Removal Rate Kg/day³	
10/20/02	2.0	8.3	0.1	
11/11/02	2.4	10.0	0.1	
11/22/02 1	4.4	18.3	0.2	
11/27/02 1	1.8	7.5	0.1	
12/4/02 1	1.2	5.0	<0.1	
12/13/02	1.4	5.8	<0.1	
12/20/02	0.6	2.5	<0.1	
12/27/02	1.2	5.0	<0.1	
1/3/03	1.9	7.9	0.1	
1/10/03	1.6	6.7	0.1	
1/16/03	0.6	2.5	<0.1	
1/29/03	0.6	2.5	<0.1	
2/7/03	0.9	3.7	<0.1	
2/11/03 8	2.5	10.4	0.1	
2/14/03 8	12.2	51	0.4	
2/28/03 8	1.6	6.7	<0.1	
3/4/03 8	10	42	0.4	
3/11/03 8	1.2	5	<0.1	
3/28/03	2.5	10.4	0.1	

Table 1. Vapor Extraction System Flow Calculations - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Date Influent Concentration (ppm)		Removal Rate Kg/day <sup>3</sup>
6/6/03	0	0	<0.1
6/18/03	1	4	<0.1
6/27/03	0	0	<0.1
7/3/03	0	0	<0.1
7/11/03	0	0	<0.1
7/17/03	0	0	<0.1
7/25/03	0	0	<0.1
7/31/03	0	0	<0.1
8/8/03	0	0	<0.1
8/14/03	0	0	<0.1
8/19/03	0	0	<0.1

### Explanation:

ppmv = parts per million (volume)

 $\mu g/l$  = micrograms/liter kg/day = kilograms/day

### Table 1. Vapor Extraction System Flow Calculations - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

#### NOTES:

<sup>&</sup>lt;sup>1</sup> ppm and ug/l reported from samples submitted to Air Toxics, Ltd, Folsom, CA.

 $<sup>^2\</sup>mu$ g/l values calculated using the following equation:  $\mu$ g/l = ppmv x molecular weight/24.055. Assumed molecular weight of gasoline = 100. Equation provided by Air Toxics Analytical Laboratory

<sup>&</sup>lt;sup>3</sup> kg/day calculations are based on system flow of 210 SCFM (standard cubic feet per minute).

<sup>&</sup>lt;sup>4</sup> Thermal oxidation unit inoperative from 12/31/01 through 2/21/02 due to mechanical failure.

<sup>&</sup>lt;sup>5</sup> Thermal oxidation unit inoperative from 3/15/02 through 3/19/02 due to mechanical failure.

<sup>&</sup>lt;sup>6</sup> SVE system inoperative between 8/16/02 and 9/9/02 in order to determine whether temporary shutdown would improve SVE system performance.

<sup>&</sup>lt;sup>7</sup> PPMV reading taken with Flame Ionization Detector (first measurement shown) and also with Photo Ionization Detector (second measurement taken).

<sup>&</sup>lt;sup>8</sup> System modified; subsequent to 2/11/03, only SVE wells 3, 5, and 7 operative.

Table 2. Flow Measurements and Vapor Concentration in Vapor Extraction Wells - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Well I.D. #	Date	Flow Velocity ft/minute	Flow Rate (SCFM) <sup>1</sup>	Vapor Concentration (ppmv)	Vapor Concentration μg/l <sup>2</sup>	TPH(G) Removal Rate grams/day
GWE/SVE-1	10/16/01	2,000	43.6	68	283	503
	11/2/01	2,250	49.1	15	62	123
	12/12/01	3,200	69.8	3	12	34
	8/1/02	2,200	48	5	21	41
	9/27/02	3,400	74.2	4.9	20	60
	10/11/02	3,600	78.5	4.3	18	58
	2/11/03	4,500	98.2	3.8	16	64
GWE/SVE-2	10/16/01	200	4.4	615	2,557	459
	11/2/01	250	5.4	223	927	204
	12/12/01	75	1.6	214	890	58
	8/1/02	150	3.3	320	1,330	179
	9/27/02	300	6.5	16.9	70	18.5
	10/11/02	350	7.6	12.2	51	16
	2/11/03	150	3.3	51.6	216	29
	2/14/03	250	5.5	50	209	47
GWE/SVE-3	10/16/01	1,200	26.2	391	1,625	1,736
	11/2/01	1,250	27	92	382	420
	12/12/01	650	14	119	495	282

Table 2. Flow Measurements and Vapor Concentration in Vapor Extraction Wells - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Well I.D. #	Date	Flow Velocity ft/minute	Flow Rate (SCFM) <sup>1</sup>	Vapor Concentration (ppmv)	Vapor Concentration μg/l <sup>2</sup>	TPH(G) Removal Rate grams/day
GWE/SVE-3	8/1/02	1,500	32.7	278	1,156	1,540
	9/27/02	1,700	37.1	5.6	23	35
	10/11/02	2,000	43.6	4.3	18	32
	2/11/03	400	8.7	55.3	231	82
	2/14/03	2,000	43.6	17.2	72	128
GWE/SVE-4	10/16/01	90	2.0	16	67	5.5
	11/2/01	100	2.2	17	71	6
	12/12/01	50	1.1	2	8	0.4
	8/1/02	0	0	54	224	0
	9/27/02	0	0	0	0	0
	10/11/02	0	0	0	0	0
	2/11/03	3,000	65.4	7.6	32	85
GWE/SVE-5	10/16/01	550	12.0	12	50	24
	11/2/01	175	3.8	3	12	2
	12/12/01	150	3.2	67	278	36
	8/1/02	2,000	43.6	0	0	0
	9/27/02	1,400	30.5	0	0	0
	10/11/02	1,500	32.7	0	0	0

Table 2. Flow Measurements and Vapor Concentration in Vapor Extraction Wells - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Well I.D. #	Date	Flow Velocity ft/minute	Flow Rate (SCFM) <sup>1</sup>	Vapor Concentration (ppmv)	Vapor Concentration μg/l <sup>2</sup>	TPH(G) Removal Rate grams/day
GWE/SVE-6	2/11/03	2,000	43.6	5.2	22	39
	10/16/01	3,300	72.0	165	686	2,013
	11/2/01	2,750	59.5	63	262	635
	12/12/01	2,600	56	169	702	1,602
	8/1/02	310	6.8	0	0	0
	9/27/02	2,800	61.1	0	0	0
	10/11/02	3,200	69.8	0	0	0
	2/11/03	3,000	65.4	3.5	15	40
GWE/SVE-7	10/16/01	1,550	33.8	254	1,056	1,455
	11/2/01	300	6.5	63	262	69
	12/12/01	200	4.3	122	507	89
	8/1/02	3,100	67.6	36.8	153	421
	9/27/02	3,400	74.2	23	96	290
	10/11/02	3,400	74.2	2.3	10	30
	2/11/03	1,500	32.7	6.9	29	39
	2/14/03	6,000	130.8	10.3	43	229
GWE/SVE-8	10/16/01	3,500	76.4	288	1,198	3,731
	11/2/01	550	11.9	153	636	308

Table 2. Flow Measurements and Vapor Concentration in Vapor Extraction Wells - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Well I.D. #	Date	Flow Velocity ft/minute	Flow Rate (SCFM) <sup>1</sup>	Vapor Concentration (ppmv)	Vapor Concentration μg/l <sup>2</sup>	TPH(G) Removal Rate grams/day
GWE/SVE-9	12/12/01	2,500	54	122	507	1,116
	8/1/02	4,500	98.2	0	0	0
	9/27/02	4,800	104.7	0	0	0
	10/11/02	4,200	91.6	0.3	1	4
	2/11/03	3,500	76.4	3.2	13	40
GWE-10	10/16/01	290	6.3	370	1,538	395
	11/2/01	100	2.2	37	154	14
	12/12/01	300	6.5	12	50	13
	8/1/02	5,500	120.0	89.4	372	1,819
	9/27/02					
	10/11/02	450	9.8	1.6	7	3
	2/11/03	500	10.9	0.8	3	1

Table 2. Flow Measurements and Vapor Concentration in Vapor Extraction Wells - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Well I.D. #	Date	Flow Velocity ft/minute	Flow Rate (SCFM) <sup>1</sup>	Vapor Concentration (ppmv)	Vapor Concentration μg/l <sup>2</sup>	TPH(G) Removal Rate grams/day
SVE-11	10/16/01	2,250	49.0	118	490	979
	11/2/01	425	9.2	36	150	56
	12/12/01	16	0.3	8	33	0.4
	8/1/02	2,600	56.7	0	0	0
	9/27/02	2,800	61.1	0	0	0
	10/11/02	3,000	65.4	0	0	0
	2/11/03	6,000	130.9	1.1	5	27
SVE-12	10/16/01	1,750	38.2	93	387	600
	11/2/01	350	7.6	18	75	23
	12/12/01	350	7.6	10	42	13
	8/1/02	2,900	63.3	5.2	22	57
	9/27/02	2,700	59.0	0	0	0
	10/11/02	3,500	76.3	1.6	7	22
	2/11/03	2,500	54.5	0.8	3	7

Table 2. Flow Measurements and Vapor Concentration in Vapor Extraction Wells - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Well I.D. #	Date	Flow Velocity ft/minute	Flow Rate (SCFM) <sup>1</sup>	Vapor Concentration (ppmv)	Vapor Concentration μg/l <sup>2</sup>	TPH(G) Removal Rate grams/day
SVE-13	10/16/01	75	1.6	499	2,074	135
	11/2/01	100	2.2	119	495	44
	12/12/01	175	3.8	32	133	21
	8/1/02	65	1.4	5	21	1.2
	9/27/02 <sup>3</sup>					
	10/11/02 <sup>3</sup>					
	2/11/03	75	1.6	1.1	5	<1

### Explanation:

SCFM = Standard Cubic Feet per Minute

ppmv = parts per million (volume)

 $\mu g/l$  = micrograms per liter

### NOTES:

<sup>&</sup>lt;sup>1</sup> Flow measured in 2" PVC vapor conduit.

 $<sup>^{2}</sup>$  µg/l values calculated using the floowing equation: µg/l = ppmv x molecular weight/24.055. Assumed molecular weight of gasoline = 100.

<sup>&</sup>lt;sup>3</sup> Well-box obstructed by vehicle on day of measurement

Table 3. Groundwater Extraction System Totalizer Readings - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Totalizer Reading (gal)	Total Discharged (gallons)	Average Flow Rate Since Previous Reading (gal/min)
5/16/01	333,054	333,054	
5/17/01	334,485	334,485	1.0
5/18/01	337,192	337,192	1.9
5/21/01	341,448	341,448	1.0
5/23/01	345,424	345,424	1.4
6/18/01	379,840	379,840	0.9
7/3/01	400,300	400,300	0.9
7/27/01	457,596	457,596	1.7
8/1/01	467,182	467,182	1.3
8/10/01	481,662	481,662	1.1
8/17/01	591,601	495,282 2	11
8/20/01	592,000	492,282	3
8/21/01	592,585	492,867	0.5
8/28/01	602,096	502,378	0.9
9/18/01	627,180	527,462	0.8
9/27/01	638,418	538,700	0.9
10/5/01	648,212	548,494	0.9
10/11/01	655,388	555,670	1.1
10/22/01	667,676	567,958	0.8
11/2/01	678,091	578,373	0.6
11/5/01	681,100 / 0 <sup>4</sup>	581,382	0.7
11/9/01	6,898	588,280	1.2
11/14/01	14,379	595,761	1.0
11/20/01	23,124	604,506	1.0
12/4/01	54,225	635,607	1.6
12/10/01	72,000	653,382	2.1

Table 3. Groundwater Extraction System Totalizer Readings - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Totalizer Reading (gal)	Total Discharged (gallons)	Average Flow Rate Since Previous Reading (gal/min)
12/17/01	93,341	674,723	2.1
12/26/01	127,051	708,433	2.6
12/31/01	149,385	730,767	3.1
1/2/02	163,000	744,382	4.7
1/11/02	166,771	748,153	5
1/15/02	190,661	772,043	4.3
1/21/02	218,788	800,170	3.1
1/29/02	254,008	835,390	3.1
2/7/02	291,624	873,006	2.9
2/14/02	322,948	904,330	3.1
2/21/02	350,361	931,743	2.7
2/27/02	381,973	963,355	3.6
3/4/02	404,348	982,730	2.7
3/11/02	436,581	1,014,963	3.2
3/19/02	473,249	1,051,631	3.2
3/29/02	522,327	1,100,709	3.4
4/5/02	554,720	1,133,102	3.2
4/19/02	607,648	1,186,030	2.6
4/26/02	705,092	1,283,474	9.7
5/2/02	729,422	1,307,804	2.8
5/6/02	764,815	1,343,197	6.1
5/8/02	771,814	1,350,196	2.4
5/16/02	799,857	1,378,239	2.4
5/21/02	817,770	1,396,152	2.5
5/29/02	848,015	1,426,397	2.6
6/7/02	881,299	1,459,681	2.6

Table 3. Groundwater Extraction System Totalizer Readings - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Totalizer Reading (gal)	Total Discharged (gallons)	Average Flow Rate Since Previous Reading (gal/min)
6/13/02	881,880	1,460,262	6
6/21/02	912,812	1,491,194	2.7
7/2/02	951,716	1,530,098	2.3
7/11/02	969,631	1,540,013	1.4
7/19/02	995,237	1,565,619	2.2
7/25/02	1,010,942	1,581,324	1.8
8/1/02	1,028,370	1,616,180	1.7
8/8/02	1,044,852	1,632,662	1.6
8/16/02	1,055,510	1,643,314	0.9
8/21/02	1,066,819	1,654,623	1.6
8/29/02	1,082,857	1,670,661	1.4
9/5/02	1,096,024	1,683,828	1.3
9/13/02	1,112,062	1,699,866	1.4
10/2/02	1,145,714	1,733,518	1.2
10/11/02	1,172,292	1,760,096	2.1
10/18/02	1,177,193	1,764,997	7
10/30/02	10,352	1,775,193	
11/1/02	13,802	1,778,799	2.4
11/5/02	19,338	1,784,335	1.0
11/11/02	25,831	1,790,828	0.8
11/22/02	54,157	1,819,154	1.8
12/4/02	72,416	1,837,413	1.1
12/13/02	89,375	1,854,372	1.3
12/20/02	134,082	1,899,079	4.4
12/30/02	190,593	1,955,590	3.9
1/3/03	215,750	1,980,747	4.4

Table 3. Groundwater Extraction System Totalizer Readings - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Totalizer Reading (gal)	Total Discharged (gallons)	Average Flow Rate Since Previous Reading (gal/min)
1/10/03	248,269	2,013,266	3.2
1/16/03	279,443	2,044,440	3.6
1/29/03	345,364	2,110,361	3.5
2/7/03	390,854	2,155,851	3.5
2/11/03	408,237	2,173,234	3.0
2/13/03	415,355	2,180,352	2.5
2/18/03	438,355	203,352	3.2
2/28/03	482,319	2,247,316	3.1
3/11/03	529,021	2,294,018	2.9
3/18/03	559,049	2,324,046	3.0
3/28/03	603,783	2,368,780	3.1
4/10/03	664,796	2,429,793	3.2
4/18/03	702,565	2,467,562	3.3
4/25/03	737,250	2,502,247	3.4
5/2/03	774,884	2,539,881	3.7
5/14/03	844,660	2,609,657	4.0
5/22/03	890,318	2,655,315	4.0
5/29/03	910,691	2,675,688	2.0
6/6/03	953,142	2,718,139	3.7
6/17/03	1,012,384	2,777,381	3.7
6/20/03	1,028,586	2,793,583	3.8
6/27/03	1,075,339	2,840,336	4.6
7/3/03	1,089,455	2,854,452	1.6
7/11/03	1,098,458	2,863,455	0.8
7/17/03	1,157,284	2,922,281	6.8
7/25/03	1,196,119	2,961,116	3.4

Table 3. Groundwater Extraction System Totalizer Readings - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Totalizer Reading (gal)	Total Discharged (gallons)	Average Flow Rate Since Previous Reading (gal/min)
7/30/03	1,217,345	2,982,342	2.9
8/8/03	1,277,728	3,042,779	4.7
8/14/03	1,306,709	3,071,706	3.3
8/19/03	1,322,407	3,087,404	2.2
8/29/03	1,332,846	3,097,843	0.7
9/5/03	1,347,945	3,112,942	1.5
9/12/03	1,351,475	3,116,742	0.4
9/26/03	1,370,697	3,135,694	0.9
10/3/03	1,379,064	3,144,061	0.8
10/10/03	1,386,120	3,151,117	0.7
10/17/03	1,391,959	3,156,956	0.6
10/24/03	1,397,544	3,162,541	0.6
10/31/03	1,403,823	3,168,820	0.6
11/7/03	1,410,468	3,175,465	0.7
11/18/03	1,412,090	3,177,087	0.1
12/5/03	1,425,363	3,190,360	0.5
12/22/03	1,436,251	3,201,248	0.4
12/30/03	1,439,644	3,204,641	0.3
1/7/04	1,440,581	3,205,578	0.1
1/14/04	1,445,512	3,210,509	0.5
1/29/04	1,489,433	3,254,430	2.0
2/13/04	1,516,076	3,281,073	1.2
2/27/04	1,544,114	3,309,111	1.4
3/3/04	1,554,424	3,319,421	1.4
3/10/04	1,568,474	3,333,471	1.4
3/16/04	1,578,867	3,343,864	1.2

Table 3. Groundwater Extraction System Totalizer Readings - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Totalizer Reading (gal)	Total Discharged (gallons)	Average Flow Rate Since Previous Reading (gal/min)
3/25/04	1,595,581	3,360,578	1.3
3/31/04	1,597,170	3,362,167	0.2
4/9/04	1,611,753	3,376,750	1.1
4/16/04	1,621,268	3,386,265	0.9
4/23/04	1,629,798	3,394,795	0.8
5/3/04	1,636,948	3,401,945	0.4
5/4/04	1,636,997	3,401,994	0 8
5/10/04	1,643,162	3,408,159	0.7
5/21/04	1,653,412	3,418,409	0.6
5/28/04	1,659,764	3,424,761	0.6
6/4/04	1,665,917	3,430,914	0.6
6/14/04	1,668,218	3,433,215	0.2
6/22/04	1,670,654	3,435,651	0.2
7/2/04	1,677,769	3,442,766	0.5
7/16/04	1,688,358	3,453,355	0.5
7/19/04	1,693,629	3,458,626	1.3
7/23/04	1,703,653	3,468,650	1.7
7/30/04	1,714,343	3,479,340	1.1
8/6/04	1,721,680	3,486,677	0.7
8/13/04	1,721,680	3,493,733	0.79
8/20/04	1,721,804	3,500,789	0.79
8/26/04	1,721,804	3,506,837	0.79
8/27/04	1,722,930	3,507,963	0.8
9/1/04	1,727,430	3,509,463	0.6
9/7/04	1,732,954	3,517,987	0.6
9/10/04	1,735,768	3,520,801	0.6

Table 3. Groundwater Extraction System Totalizer Readings - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Totalizer Reading (gal)	Total Discharged (gallons)	Average Flow Rate Since Previous Reading (gal/min)
9/17/04	1,741,255	3,526,288	0.6
9/24/04	1,744,090	3,529,123	0.3
10/1/04	1,744,238	3,529,271	0
10/4/04	1,744,264	3,529,297	010
10/5/04	1,746,297	3,531,330	1.4
10/8/04	1,749,826	3,534,859	0.8
10/11/04	1,752,815	3,537,848	0.7
10/22/04	1,754,363	3,563,352	1.611
10/29/04	1,756,580	3,579,480	1.611
11/4/04	622	3,593,416	1.6 <sup>11, 12</sup>
11/5/04	2,534	3,595,328	1.4
11/12/04	16,804	3,609,598	1.4
12/6/04	64,735	3,657,529	1.4
12/17/04	87,937	3,680,731	2.0
12/23/04	106,802	3,699,596	1.4
12/30/04	130,647	3,723,441	2.4
1/5/05	156,935	3,749,729	3.13
1/6/05	163,038	3,755,832	3.39
1/14/05	188,997	3,781,791	2.27
1/28/05	206,004	3,798,798	0.84
2/7/05	257,671	3,850,465	3.61
2/14/05	275,063	3,867,857	1.70
3/4/05	347,248	3,940,042	2.78
3/10/05	378,996	3,971,790	3.73
3/21/05	425,475	4,018,269	2.96
4/1/05	471,716	4,064,510	2.90

Table 3. Groundwater Extraction System Totalizer Readings - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Date	Totalizer Reading (gal)	Total Discharged (gallons)	Average Flow Rate Since Previous Reading (gal/min)
4/6/05	486,288	4,079,082	2.02
4/8/05	497,476	4,090,270	3.88
4/15/05	527,243	4,120,037	2.95
4/22/05	553,539	4,146,333	2.61
5/2/05	602,308	4,195,102	3.39
5/6/05	613,012	4,205,806	1.86
5/16/05	651,533	4,244,327	2.50
7/5/05	651,533	4,244,327	0.00
7/22/05	739,986	4,332,780	3.61
7/29/05	773,192	4,365,986	3.29
8/5/05	801,337	4,394,131	2.79
8/12/05	827,552	4,420,346	2.60
8/19/05	852,397	4,445,191	2.46
8/21/05	855,601	4,448,395	1.11
8/26/05	875,312	4,468,106	2.73
9/2/05	892,192	4,484,986	1.67
9/9/05	908,580	4,501,374	1.62
9/19/05	923,094	4,515,888	1.01
9/23/05	936,118	4,528,912	2.26
10/5/05	953,125	4,545,919	0.98

# NOTES:

<sup>&</sup>lt;sup>1</sup> 8/17/01 meter reading is incorrect due to system malfunction.

<sup>&</sup>lt;sup>2</sup> Discharge for period between 8/17/01 and 8/20/01 is calculated at 1 gallon per minute. <sup>3</sup> System inoperative between 8/17/01 and 8/20/01.

New flow totalizer installed 11/5/01 at 1:00 PM.
 System inoperative between 1/02/02 and 1/10/02 for carbon vessel recharge and carbon vessel repair.

<sup>&</sup>lt;sup>6</sup> System inoperative between 6/7/02 and 6/13/02 due to compressor failure.

<sup>&</sup>lt;sup>7</sup> Totalizer malfunctioned and reset to zero on 10/18/02.

<sup>&</sup>lt;sup>8</sup> System inoperative between 5/3/04 and 5/4/04 due to compressor malfunction.

Groundwater Extraction System Totalizer Readings - Redwood Oil Company Bulk Plant, 455 Yolanda, Table 3. Santa Rosa, California

System operating but totalizer inoperative between 8/6/04 and 8/26/04. Average flow rate for the quarter was used to estimate actual flow rate.
 System inoperative between 10/1/04 and 10/4/04.
 System operating but totalizer inoperative. Average flow rate for the quarter was used to estimate actual flow rate.
 New flow totalizer installed 11/4/04. Readings begin at 622 gallons.

Table 4. Influent Analytical Results - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Sample ID	Date	TPPH(G)	TPH(D)	Benzene	Toluene	Ethyl Benzene	Xylenes	МТВЕ
		<			PPB			->
Influent	2/2/011			310	56	84	130	
Influent	2/8/011	9,300	<50					38,000
Influent	5/17/01	6,500	<50	1.3	3.2	2.2	7.3	
Influent	5/21/01	2,500	210	<12.5	<12.5	<12.5	<12.5	4,200 2
Influent A	8/13/01	12,000	1900	490	400	95	1000	8,200 3
Influent B	8/13/01	1,500	1200	130	7.7	5.1	55	1,900 4
Influent A	8/23/01	1,600	1400	170	6.1	4.1	26	2,200 5
Influent B	8/23/01	2,000	1800	72	18	<2.5	83	6,500 6
Influent A	11/20/01	1,900	720	48	16	<5	93	4,500 7
Influent B	11/20/01	2,700	1,500	52	53	<25	140	3,700 8
Influent A	2/14/02	570	1,800	50	6.1	28	78	310 9
Influent B	2/14/02	74	110	1.4	7.9	< 0.50	6.9	3,600 10
Influent A	5/6/02	84	160	4.9	0.58	1.6	3.9	690 <sup>2</sup>
Influent B	5/6/02	940	1,300	<5	220	14	111	1,600 <sup>2</sup>
Influent A	8/8/02	530	300	11	7.6	2.5	18	420 <sup>2</sup>
Influent B	8/8/02	460	970	5.9	3.6	1.1	10	690 <sup>2</sup>

Table 4. Influent Analytical Results - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

Sample ID	Date	TPPH(G)	TPH(D)	Benzene	Toluene	Ethyl Benzene	Xylenes	MTBE
		<			PPB			->
Influent A	11/05/02	730	380	<0.5	<0.5	<0.5	<1	3,700 11
Influent B	11/05/02	84	580	7.8	4.4	<2.5	23	780 <sup>2</sup>
Influent A	2/18/03	360	240	5.6	<0.5	0.71	1.5	4,300 <sup>2</sup>
Influent B	2/18/03	1,300	<63	<2.5	<2.5	<2.5	<2.5	1,900 <sup>2</sup>
Influent A	5/14/03	120	530	1.4	<1	<1	<1	1,100 12
Influent B	5/14/03	440	200	4.9	2.2	1.3	8.5	1,200 <sup>2</sup>
Influent A	8/14/03	220	230	2.0	<0.5	0.69	3.1	360 <sup>13</sup>
Influent B	8/14/03	210	330	6.6	<0.5	0.62	<1	280 13
Influent	12/22/03	160	630	13	<0.5	<0.5	1.3	110 14
Influent	3/16/04	240	250	7.0	0.52	<1	4.5	390
Influent	5/11/04	540	<50	<5	<5	<5	<5	760
Influent	7/22/04	410	<50	8.4	<5	<5	<5	600
Influent	10/4/04	200	1,800	30	<2.5	<2.5	<5	190
Influent	1/5/05	<50	<50 <sup>15</sup>	10	<2.5	<2.5	6.7	530
Influent	4/6/05	260	190	<2.5	<2.5	<2.5	<2.5	370
Influent	7/6/05	270	350	12	<2.5	<2.5	2.7	360

#### Table 4. Influent Analytical Results - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

### Explanation:

total purgeable petroleum hydrocarbons as gasoline TPPH(G) =TPH(D) =total purgeable petroleum hydrocarbons as diesel

MTBE = methyl tertiary butyl ether

part per billion ppb tertiary butanol TBA =

TAME = tertiary amyl methyl ether

### NOTES:

Samples dated 2/2/01 and 2/8/01 collected by Earth Engineers. 2/8/01 sample was analyzed for VOCs by EPA Method 8260. Consult analytical laboratory results for other analytes detected.

<sup>&</sup>lt;sup>2</sup> Other oxygenates not detected.

<sup>&</sup>lt;sup>3</sup> TAME and TBA also detected at 190 and 2,600 ppb respectively. Other oxygenates not detected.

<sup>&</sup>lt;sup>4</sup> TBA also detected at 950 ppb. Other oxygenates not detected.

<sup>&</sup>lt;sup>5</sup> TBA also detected at 810 ppb. Other oxygenates not detected.

<sup>&</sup>lt;sup>6</sup> TBA also detected at 1,600 ppb. Other oxygenates not detected.

<sup>&</sup>lt;sup>7</sup> TBA also detected at 640 ppb. Other oxygenates not detected.

<sup>&</sup>lt;sup>8</sup> TBA also detected at 810 ppb. Other oxygenates not detected.

<sup>&</sup>lt;sup>9</sup> TAME and 1,2 Dichloroethane also detected at 5.7 and 2.8 ppb respectively. Other oxygenates not detected.

<sup>&</sup>lt;sup>10</sup> TAME also detected at 66 ppb. Other oxygenates not detected.

<sup>&</sup>lt;sup>11</sup> TBA also detected at 760 ppb. Other oxygenates not detected.

<sup>&</sup>lt;sup>12</sup> TBA also detected at 760 ppb. Other oxygenates not detected.

TBA also detected at 350 ppb. Other oxygenates not detected.

TBA detected in Influent A and Influent B at 80 and 93 ppb respectively. Other oxygenates not detected.

<sup>&</sup>lt;sup>14</sup> TBA detected in Influent sample at 44 ppb. Other oxygenates not detected.

<sup>&</sup>lt;sup>15</sup> 430 ppb light Oil is in the sample (C12-C36. No Diesel pattern.

Table 5: Water Levels in Pumping Wells - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, CA

Date	PMCS #1	PMCS #2	PMCS #3	PMCS #4	PMCS #5	PMCS #6	GWE/ SVE #1	GWE/ SVE #2	GWE/ SVE #3	GWE/ SVE #4	GWE/ SVE #5	GWE/ SVE #6	GWE/ SVE #7	GWE/S VE #8	GWE/S VE #9	GWE #10
		<					-Depth to	Water (Ft)							>	
2/15/01	33.9	28.2	26.3	26.1	26.0	25.35	-	-	-	-	-	-	-	-	-	-
5/16/01	15.16	15.31	16.05	16.24	14.72	13.32	-	-	-	-	-	-	-	-	-	-
5/17/01	-	23.53	26.15	22.75	24.88	24.87	-	-	-	-	-	-	-	-	-	-
5/21/01	-	23.52	26.15	24.82	24.91	24.90	-	-	-	-	-	-	-	-	-	-
6/18/01	-	23.5	26.12	24.83	24.92	24.90	-	-	-	-	-	-	-	-	-	-
7/5/01	-	-	-	-	-	-	24.15	24.50	20.55	24.01	24.21	23.48	25.22	23.19	22.84	15.51
7/27/01	24.62	23.53	26.08	24.80	24.88	24.87	24.08	29.40	20.42	23.90	24.10	23.41	25.09	23.10	23.01	15.45
8/14/01	-	23.51	26.11	22.89	24.89	24.90	22.30	28.75	22.2	23.81	-	-	-	-	-	-
8/17/01	24.80	23.62	26.12	24.79	24.90	24.92	-	-	-	-	-	-	-	-	-	-
9/18/01	-	23.49	26.12	24.81	24.92	24.92	23.96	29.51	20.53	23.90	24.10	23.46	25.11	23.18	23.01	15.81
9/27/01	-	23.51	26.10	24.10	25.42	25.40	-	-	-	-	-	-	-	-	-	-
10/11/01	-	-	-	-	-	-	24.02	29.41	20.52	23.90	24.12	23.46	25.14	23.18	22.91	15.45
11/2/01	24.80	23.50	26.10	25.40	25.40	25.45	24.05	29.45	20.50	23.95	24.15	23.40	25.14	23.15	22.96	15.40
12/4/01	24.62	23.60	26.00	25.70	25.80	25.70	24.03	29.40	20.40	23.80	24.15	23.30	25.30	23.20	22.90	15.50
2/28/02		23.5	26.0	22.5	25.0	25.0	24.0	22.0	22.6	24.0	23.3	23.3	24.0	23.0	23.0	15.0
5/8/02		23.51	26.42	23.10	24.86	23.70	23.97	14.65	22.05	23.80	24.15	23.34	22.19	22.27	11.85	12.16
8/1/02	24.60	23.65	30.60	30.35	25.40	24.80	24.00	29.40	22.50	23.90	24.10	23.35	23.95	23.07	22.9	15.36
8/21/02	24.60	23.65	30.60	30.35	25.40	24.80	24.00	29.40	22.50	23.90	24.10	23.35	23.95	23.07	22.9	15.36

Table 5: Water Levels in Pumping Wells - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, CA

Date	PMCS #1	PMCS #2	PMCS #3	PMCS #4	PMCS #5	PMCS #6	GWE/ SVE #1	GWE/ SVE #2	GWE/ SVE #3	GWE/ SVE #4	GWE/ SVE #5	GWE/ SVE #6	GWE/ SVE #7	GWE/S VE #8	GWE/S VE #9	GWE #10
		<					-Depth to	Water (Ft)-							>	
11/1/02	24.60	23.65	30.60	30.35	25.40	24.80	24.00	29.40	22.50	23.90	24.10	23.35	23.95	23.07	22.9	15.36
1/29/02	24.60	23.65	30.60	30.35	25.40	24.80	24.00	29.40	22.50	23.90	24.10	23.35	23.95	23.07	22.9	15.36
4/25/03	24.60	23.65	30.60	30.35	25.40	24.80	24.00	29.40	22.50	23.90	24.10	23.35	23.95	23.07	22.9	15.36
7/25/03	24.60	23.65	30.60	30.35	25.40	24.80	24.00	29.40	22.50	23.90	24.10	23.35	23.95	23.07	22.9	15.36
3/16/04	24.60	23.65	30.60	30.35	25.40	24.80	24.00	29.40	22.50	23.90	24.10	23.35	23.95	23.07	22.9	15.36
10/8/04		23.50	28.06	17.83		24.56	23.95	29.35	22.50	23.30	24.10	23.30	25.25	23.02	22.85	
4/22/05	26.30	23.44	25.95	12.19	24.72	18.61	10.55	29.50	10.51	8.80	24.23	12.45	22.76	23.15	22.90	
9/9/05		26.02	14.12	23.44	24.78	24.40			22.62			23.45	25.30	23.15		15.50

Note: If water level in pumping well is below Top of Pump, measurement is to Top of Pump only.

Note: System inoperative from 4/30/01 to 5/16/01. PMCS wells reactivated 5/16/01.

Note: Water levels shown in table increased by 1 ft from water levels measured in field due to depth of casing in well boxes.

Main GWE system reactivated 6/15/01.

Table 6. Sparge Point Flow Rates - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

DATE	AS #1	AS #2	AS #3	AS #4	AS #5	AS #6	AS #7	AS #8	AS #9	AS #10	AS #11	AS #12	AS #13	AS #14
			<		Flo	w Rate (Sta	ndard Cubi	c Feet Per M	inute)		·	>		
7/5/01	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2
7/23/01	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2
7/27/01	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2
8/1/01	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2
8/10/01	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2
8/28/01	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2
9/10/01	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2
9/27/01	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2
10/4/01	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2
10/9/01	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2	≤2
10/16/01	≤2	≤2	≤2	≤2	≤2	4	≤2	4	≤2	10	4	≤2	≤2	≤2
10/25/01	≤2	≤2	6	3	5	6	3	4	4	7	10	8	4	8
11/2/01	5		6	6	6	7	2	5	5	7	6	6	6	6
11/20/01	5		7	6	6	7	2	7	7	5	6	6	7	6
12/12/01	5		7	4	6	9	2	6	7	6	9	7	8	7
2/7/02	5		5	5	7	8	3	5	6	5	6	5	6	5
2/21/02	8		5	5	5	4	6	4	8	6	8	5	8	8
3/5/02	8		5	5	4	5	5	5	8	5	8	5	8	8
3/14/02	8		5	5	5	4	6	4	8	6	8	5	8	8

Table 6. Sparge Point Flow Rates - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

DATE	AS #1	AS #2	AS #3	AS #4	AS #5	AS #6	AS #7	AS #8	AS #9	AS #10	AS #11	AS #12	AS #13	AS #14
	<			Flow Ra	te (Standard	l Cubic Fee	t Per Minut	e)		>				
4/5/02	8		8	10	15	2	20	8	7	7	9	10	8	9
4/19/02	8		8	10	15	2	20	8	7	7	9	10	8	9
5/2/02	8		8	10	12	4	16	8	5	5	10	10	6	10
5/16/02	6		6	12	8	4	16	8	6	6	10	8	6	8
5/21/02	8		10	15	2	18	8	6	6	10	10	8	8	10
6/7/02	6		2	4	6	2	6	4	6	8	8	8		2
6/20/02	6		2	4	6	2	6	4	6	8	8	8		2
7/19/02	6		2	4	6	2	6	4	6	8	8	8		2
8/1/02	7		7	4	2	4	2	4	4	7	8	8		6
8/16/02 1	7	4	6	4	2	4	3	5	5	6	8	8	2	6
9/19/02	6	4	6	5	2	4	4	5	5	4	6	8	2	5
11/11/02	5	6	8	6	2	5	6	2	2	5	6	4	4	6
11/27/02	4	2	4	6	2	4	2	4	2	4	2	8	4	4
12/13/02	4	6	2	4	8	8	4	6	4	8	4	2	2	4
1/16/03	5	2	4	5	3	4	2	4	4	6	2	6	2	2
2/14/03 <sup>2</sup>	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	4	0 - 2	8	0 - 2	0 - 2
2/28/03	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	4	2	4	2
3/28/03	2	2	2	2	2	2	2	2	2	2	2	2	2	2
4/24/03	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2

Table 6. Sparge Point Flow Rates - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

5/8/03	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	5	0 - 2	0 - 2	4
7/11/03	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2
8/29/03	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2	0 - 2
DATE	Operating Air Sparge Points					_	AS Point FM)	Total l (CF		Operatii	ng Hours		Notes	
9/12/03		A	S #1 - AS #	±14		0	- 1	0 -	14			all points set to 1cfm or less		
9/26/03		A	S #1 - AS #	±14		0	- 1	0 -	14	33	35			
10/3/03		A	S #1 - AS #	±14		0	- 1	0 -	14	10	66			
10/10/03		A	S #1 - AS #	±14		0	- 1	0 -	14	10	68			
10/17/03		A	S #1 - AS #	±14		0	- 1	0 - 14		158				
10/24/03		A	S #1 - AS #	±14		0	- 1	0 -	14	10	68			
10/31/03		A	S #1 - AS #	±14		0	- 1	0 -	14	10	67			
11/19/03		A	S #1 - AS #	±14		0	- 1	0 -	14	4:	56			
12/22/03		A	S #1 - AS #	±14		0	- 1	0 -	14	60	)9			
1/7/04		A	S #1 - AS #	±14		0	- 1	0 - 14				flow meter inoperative		ve
1/14/04		A	S #1 - AS #	±14		0	- 1	0 -	14	-		flow met	er inoperati	ve
1/29/04	AS #1 - AS #14			0	- 1	0 -	14	(	)		_	_		
2/13/04	AS #1 - AS #14			0	- 1	0 -	14	719						
2/27/04	AS #1 - AS #14			0	- 1	0 - 14		332						
3/3/04	AS #1 - AS #14			0	- 1	0 -	14	12	24					

Table 6. Sparge Point Flow Rates - Redwood Oil Company Bulk Plant, 455 Yolanda, Santa Rosa, California

DATE	Operating Air Sparge Points	Flow per AS Point (CFM)	Total Flow (CFM)	Operating Hours	Notes
3/10/04	AS #1 - AS #14	0 - 1	0 - 14	0	
3/16/04	AS #1 - AS #14	0 - 1	0 - 14	0	
3/25/04	AS #1 - AS #14	0 - 1	0 - 14	0	
3/31/04	AS #1 - AS #14	0 - 1	0 - 14	0	
4/9/04	AS #1 - AS #14	0 - 1	0 - 14	0	
5/4/04	AS #1 - AS #14	0 - 1	0 - 14		flow meter inoperative
6/4/04	AS #1 - AS #14	0 - 1	0 - 14	746	
7/9/04	AS #1 - AS #14	0 - 1	0 - 14		flow meter inoperative
8/2/04	AS #1 - AS #14	0 - 1	0 - 14	739	
8/26/04	AS #1 - AS #14	0 - 1	0 - 14	547	
12/30/04	AS #1 - AS #14	0 - 1	0 - 14	2643	readings switched to quarterly
3/21/05	AS #1 - AS #14	0 - 1	0 - 14	1508	
4/24/05	AS #1 - AS #14	0 - 1	0 - 14	699	system deactivated

Notes: Two standard cubic feet per minute is the lowest reading available on flow meter

AS system inoperative between 8/16/02 and 9/9/02 during cyclic shutdown of SVE system

System functioning but flow meters inoperative

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)		Interval	Interval	Grout	
		<u> </u>						Interval	
MW-1	01/11/91		102.77			9 - 24	7 - 24	0 - 7	
	02/08/91								
	03/08/91								
	06/13/91			80.75	0.00				
	07/09/91	22.22		80.55	0.00				
	08/01/91			80.77	0.00				
	08/29/91	21.73		81.04					
	09/11/91			81.02	0.00				
	10/08/91			80.73	0.00				
	11/08/91			80.54		4			
	12/11/91				0.00				
	01/13/92			81.36					
	02/11/92	20.25		82.52	0.00				
	03/11/92	12.79		89.98 89.01					
	04/13/92 05/15/92	13.76 15.49		87.28	0.00				
	05/15/92	16.85		85.92	0.00				
	07/16/92	17.74	4	85.03	0.00				
	08/18/92			85.21	0.00				
	09/18/92			84.15	0.00				
	12/08/92			84.39	0.00				
	03/10/93			89.48	0.00				
	06/04/93			90.00	0.00				
	10/14/93	23.66		79.11	0.00				
	04/11/94	14.58		88.19	0.00				
	10/19/94			88.26					
	04/11/95			93.59					
	03/06/96			92.61	0.00				
	10/14/96				0.00				Top of casing elevations re-surveyed.
	04/09/97			92.03	0.00				
	10/29/97			89.50					
	04/07/98			94.72	0.00				
	10/07/98			91.27	0.00	4			
	04/07/99	8.71		94.07	0.00		1		

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)		Interval	Interval	Grout	
								Interval	
MW-1	10/19/99		102.78	90.80	0.00	9 - 24	7 - 24	0 - 7	
	04/26/00				0.00				Well inaccessible due to construction activities.
	10/30/00				0.00				Top of casing elevations re-surveyed.
	02/01/01	11.28		134.88	0.00				
	04/23/01	14.29		131.87	0.00				
	07/23/01	14.88		131.28	0.00				
	10/23/01	16.46		129.70	0.00				
	01/21/02	12.77	148.81	136.04	0.00				Top of casing elevations were surveyed for EDF compliance.
	04/25/02	12.80	1	136.01	0.00				
	07/22/02	13.20		135.61	0.00				
	10/22/02	13.76		135.05	0.00				
	01/27/03	13.00		135.81	0.00				
	04/21/03	12.85	1	135.96	0.00				
	07/21/03	13.36	1	135.45	0.00				
	01/20/04	10.04		138.77	0.00				
	07/19/04	13.04		135.77	0.00				
	01/18/05	9.96		138.85	0.00				
	07/12/05	9.40		139.41	0.00				
	09/09/05	10.39		138.42	0.00				
MW-2	01/11/91	21.36	102.18		0.00	10 - 25	7.5 - 25	0 - 7.5	
	02/08/91	18.24		83.94	0.00				
	03/08/91			85.66	0.00				
	06/13/91	20.95		81.23	0.00				
	07/09/91	20.98		81.20	0.00				
	08/01/91	20.98		81.20	0.00				
	08/29/91	21.28		80.90	0.00				
	09/11/91	21.36		80.82	0.00				
	10/08/91	21.83		80.25	0.22				
	11/08/91	20.56		81.62	0.00				
	12/11/91	21.08		81.10	0.00				
	01/13/92	18.56		83.62	0.00				
	02/11/92	14.30		87.88	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)		Interval	Interval	Grout	
								Interval	
MW-2	03/11/92	11.81			0.00	10 - 25	7.5 - 25	0 - 7.5	
	04/13/92	13.23		88.95	0.00				
	05/15/92	15.09		87.09	0.00				
	06/15/92	16.95		85.23	0.00				
	07/16/92	17.96		84.22	0.00				
	08/18/92	17.76		84.42	0.00				
	09/18/92	18.75	-	83.43	0.00				
	12/08/92	14.66		87.52	0.00				
	03/10/93	12.80		89.38	0.00				
	06/04/93	13.25	-	88.93	0.00				
	10/14/93	16.20		85.98	0.00				
	04/11/94	14.85		87.33	0.00				
	10/19/94	15.04		87.14	0.00	,			
	04/11/95	9.77		92.41	0.00	,			
	03/06/96		-	92.06	0.00				
	10/14/96			89.74	0.00				
	04/10/97	10.79		91.40	0.00				
	10/28/97	13.32	-	88.87	0.00				
	04/07/98			94.17	0.00				
	10/07/98			90.55	0.00				
	04/07/99		-	93.40	0.00				
	10/19/99			90.14	0.00				
	04/26/00								Well inaccessible due to construction activities.
	10/30/00				0.00				Top of casing elevations re-surveyed.
	02/01/01	10.70		134.62	0.00				
	04/23/01	13.74		131.58	0.00				
	07/23/01	14.22		131.10	0.00				
	10/23/01	16.04		129.28	0.00				
	01/21/02	13.36	-1	134.61	0.00	ļ			
	04/25/02	13.80		134.17	0.00	ļ			
	07/22/02	13.81		134.16	0.00	ļ			
	10/22/02			134.15	0.00				T. C : 1 /: 10 PPP
	01/27/03	13.18	147.97	134.79	0.00				Top of casing elevations were surveyed for EDF
									compliance.

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)		Interval	Interval	Grout	
								Interval	
MW-2	04/21/03		147.97		0.00	_1	7.5 - 25	0 - 7.5	
	07/21/03			134.96	0.00				
	01/20/04			136.16	0.00				
	07/19/04	12.84		135.13	0.00				
	01/18/05			136.83	0.00				
	07/12/05			136.95	0.00				
	09/09/05	11.92		136.05	0.00				
7.577.0	01/11/01	I	10104	T	ı	10.00	15.00	1 0 15	
MW-3	01/11/91		101.94			18 - 33	17 - 33	0 - 17	
	02/08/91	20.20		72.66					
	03/08/91 06/13/91	28.28	-	73.66	0.00				
	06/13/91		-						
	08/01/91								
	08/29/91		-						
	09/11/91		-			-			
	10/08/91								
	11/08/91		1			•			
	12/11/91								
	01/13/92		1						
	02/11/92		1	83.12	0.00	1			
	03/11/92	11.76		90.18	0.00				
	04/13/92			89.69	0.00				
	05/15/92			86.59	0.00	_1			
	06/15/92			84.33	0.00	_1			
	07/16/92			82.08	0.00	_1			
	08/18/92			82.28	0.00				
	10/18/92			75.94	0.00	_1			
	12/08/92			84.70	0.00	-1			
	03/10/93		-1	87.34	0.00				
	06/04/93			87.99	0.00				
	10/14/93			05.26		4			
	04/11/94			85.36	0.00				
	10/19/94	16.01		85.93	0.00				]

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)	. ,	Interval	Interval	Grout	
								Interval	
MW-3	04/11/95				0.00	18 - 33	17 - 33	0 - 17	
	03/06/96			90.22	0.00				
	10/14/96				0.00				
	04/10/97	12.08		89.90	0.01				
	10/29/97	16.02		85.99	0.02				
	04/07/98		4	92.00	0.00				
	10/07/98			89.31	0.00				
	04/07/99			92.27	0.00				
	10/19/99			88.82	0.00				
	04/26/00					,			Well inaccessible due to construction activities.
	10/30/00		145.10			,			Well plugged at seven feet, no water.
	02/01/01	12.33		132.77	0.00	,			
	04/23/01					,			Well was inaccessible
	07/23/01			130.12	0.00	,			
	10/23/01			128.10	0.00				
	01/21/02	13.67	147.75	134.08	0.00				Top of casing elevations were surveyed for EDF
									compliance.
	04/25/02			133.25	0.00	,			
	07/22/02			132.79	0.00				
	10/22/02			132.53	0.00				
	01/27/03			133.54	0.00				
	04/21/03			134.28	0.00				
	07/21/03			133.32	0.00				
	01/20/04			135.75	0.00				
	07/19/04			133.72	0.00				
	01/18/05			136.64	0.00				
	07/12/05	11.68		136.07	0.00				
2.5337.4	01/11/01	1	101.47	1		10.05	7 25	0.7	
MW-4	01/11/91		101.47			10 - 25	7 - 25	0 - 7	
	02/08/91								
	03/08/91		-						
	06/13/91								
	07/09/91								
	08/01/91		<u> </u>						

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)		Interval	Interval	Grout	
		·						Interval	
MW-4	08/29/91		101.47			10 - 25	7 - 25	0 - 7	
	09/11/91								
	10/08/91								
	11/08/91								
	12/11/91								
	01/13/92	24.47	4	77.00	0.00				
	02/11/92	26.06		75.41	0.00				
	03/11/92	23.46		78.01	0.00				
	04/13/92	24.25		77.22	0.00				
	05/15/92								
	06/15/92								
	07/16/92								
	08/18/92								
	09/18/92								
	12/08/92								
	03/10/93		ļ						
	06/04/93		ļ						
	10/14/93		ļ						
	04/11/94								
	10/19/94								
	04/11/95								
	03/06/96			84.95	0.00				
	10/14/96		101.70		0.00				
	04/10/97	16.02		85.68	0.00				
	10/29/97 04/07/98	21.61	ł	80.09 90.40	0.00	_1			
	10/07/98			86.17	0.00				
	04/07/99			89.75	0.00	_1			
	10/19/99			86.55	0.00	_1			
	04/26/00		4	91.32	0.00				
	06/01/00					-			
	10/30/00		145.47	131.69	0.00	1			Top of casing elevations were surveyed.
	02/01/01			131.09	0.00				Top of casing elevations were surveyed.
	04/23/01			126.20					
	04/23/01	19.27		120.20	0.00	l		<u> </u>	

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)	, , ,	msl)	. ,	Interval	Interval	Grout	
								Interval	
MW-4	07/23/01				0.00	10 - 25	7 - 25	0 - 7	
	10/23/01	19.88		125.59					
	01/21/02	13.62	148.12	134.50	0.00				Top of casing elevations were surveyed for EDF
									compliance.
	04/25/02	14.47		133.65	0.00				
	07/22/02	15.57		132.55	0.00				
	10/22/02	17.23		130.89	0.00				
	01/27/03	13.00		135.12	0.00				
	04/21/03	13.42		134.70	0.00				
	07/21/03	14.15		133.97	0.00				
	01/20/04	11.67		136.45	0.00				
	07/19/04 01/18/05	14.47 11.31		133.65 136.81	0.00				
	07/12/05			136.81	0.00				
	07/12/03	11.33		130.39	0.00				
MW-5	06/13/91	25.84	101.37	75.53	0.00	34.5 - 44.5	32.5 - 44.5	0 - 32.5	
1,1,1	07/09/91	25.98		75.39	0.00	1	22.0 11.0	0 32.3	
	08/01/91	23.22		78.15	0.00				
	08/29/91	22.79		78.58	0.00				
	09/11/91	22.58		78.79	0.00				
	10/08/91	27.46		73.91	0.00				
	11/08/91	24.36		77.01	0.00				
	12/11/91	23.35		78.02	0.00				
	01/13/92	23.96		77.41	0.00				
	02/11/92	23.67		77.70	0.00				
	03/11/92	22.01		79.36	0.00				
	04/13/92	21.50		79.87	0.00				
	05/15/92	18.96		82.41	0.00				
	06/15/92	18.72		82.65	0.00	,			
	07/16/92	19.88		81.49	0.00				
	08/18/92	19.38		81.99	0.00				
	09/18/92			81.77	0.00				
	12/08/92			81.33	0.00				
	03/10/93	16.60		84.77	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

e 06/04/93 0/14/93	msl)		1)			Sand Pack	Bentonite/	Notes
			msl)		Interval	Interval	Grout	
							Interval	
0/14/93	15.96	101.37	85.41	0.00	34.5 - 44.5	32.5 - 44.5	0 - 32.5	
	18.68		82.69	0.00				
04/11/94	14.46		86.91	0.00				
0/19/94	15.56		85.81	0.00				
4/11/95	9.52		91.85	0.00				
3/06/96	10.60		90.77	0.00				
0/14/96	11.81		89.53	0.00				
4/09/97	10.08		91.26	0.00				
0/29/97	15.05		86.29	0.00				
4/07/98	8.01		93.33	0.00				
0/07/98	9.82		91.52	0.00				
4/07/99	9.12		92.22	0.00				
0/19/99	12.96		88.38	0.00				
4/26/00	9.28		92.06	0.00				
0/30/00		145.73						Well inaccessible due to area flooding
2/01/01	11.52		134.21	0.00				
04/23/01	15.25		130.48	0.00				
7/23/01	13.22		132.51	0.00	]			
0/23/01					]			
01/21/02	12.50	148.38	135.88	0.00				Top of casing elevations were surveyed for EDF compliance.
04/25/02	12.02		136.36	0.00				
7/22/02	11.00		137.38	0.00				
0/22/02	11.40		136.98	0.00				
01/27/03	10.78		137.60	0.00				
04/21/03	9.15		139.23	0.00				
1/20/04	8.00		140.38	0.00				
7/19/04	10.53		137.85	0.00				
1/18/05	10.09		138.29					
7/12/05	7.11		141.27		4			
0/ 01/ 04/ 04/ 04/ 01/	/23/01 /21/02 /25/02 /22/02 /22/02 /27/03 /21/03 /20/04 /19/04 /18/05	/23/01         13.15           /21/02         12.50           /25/02         12.02           /22/02         11.00           /22/02         11.40           /27/03         10.78           /21/03         9.15           /20/04         8.00           /19/04         10.53           /18/05         10.09	723/01     13.15       721/02     12.50     148.38       725/02     12.02       722/02     11.00       722/02     11.40       727/03     10.78       721/03     9.15       720/04     8.00       719/04     10.53       718/05     10.09	/23/01         13.15         132.58           /21/02         12.50         148.38         135.88           /25/02         12.02         136.36           /22/02         11.00         137.38           /22/02         11.40         136.98           /27/03         10.78         137.60           /21/03         9.15         139.23           /20/04         8.00         140.38           /19/04         10.53         137.85           /18/05         10.09         138.29	/23/01         13.15         132.58         0.00           /21/02         12.50         148.38         135.88         0.00           /25/02         12.02         136.36         0.00           /22/02         11.00         137.38         0.00           /22/02         11.40         136.98         0.00           /27/03         10.78         137.60         0.00           /21/03         9.15         139.23         0.00           /20/04         8.00         140.38         0.00           /19/04         10.53         137.85         0.00           /18/05         10.09         138.29         0.00	/23/01         13.15         132.58         0.00           /21/02         12.50         148.38         135.88         0.00           /25/02         12.02         136.36         0.00           /22/02         11.00         137.38         0.00           /22/02         11.40         136.98         0.00           /27/03         10.78         137.60         0.00           /21/03         9.15         139.23         0.00           /20/04         8.00         140.38         0.00           /19/04         10.53         137.85         0.00           /18/05         10.09         138.29         0.00	723/01         13.15         132.58         0.00           721/02         12.50         148.38         135.88         0.00           725/02         12.02         136.36         0.00           722/02         11.00         137.38         0.00           722/02         11.40         136.98         0.00           727/03         10.78         137.60         0.00           721/03         9.15         139.23         0.00           720/04         8.00         140.38         0.00           719/04         10.53         137.85         0.00           718/05         10.09         138.29         0.00	/23/01         13.15         132.58         0.00           /21/02         12.50         148.38         135.88         0.00           /25/02         12.02         136.36         0.00           /22/02         11.00         137.38         0.00           /22/02         11.40         136.98         0.00           /27/03         10.78         137.60         0.00           /21/03         9.15         139.23         0.00           /20/04         8.00         140.38         0.00           /19/04         10.53         137.85         0.00           /18/05         10.09         138.29         0.00

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)		Interval	Interval	Grout	
								Interval	
MW-5A	10/14/96				0.00	50 - 60	49 - 60	0 - 49	
	04/10/97	10.16		91.21	0.00				
	10/29/97	16.80		84.57	0.00				
	04/07/98			91.73	0.00				
	10/07/98			91.28	0.00				
	04/07/99			93.82	0.00				
	10/19/99								Well casing was damaged.
	04/26/00				0.00				
	10/30/00		145.70						Well inaccessible due to area flooding
	02/01/01	11.17		134.53	0.00				
	04/23/01	11.75		133.95	0.00				
	07/23/01	12.58		133.12	0.00				
	10/23/01	13.71	140.25	131.99	0.00				T. C. I. I. I. I.C. EDE
	01/21/02	12.55	148.35	135.80	0.00				Top of casing elevations were surveyed for EDF
	04/25/02	11.45		136.90	0.00				compliance.
	07/22/02	10.75		130.90	0.00				
	10/22/02	10.73		137.45	0.00				
	01/27/03	10.31		138.04	0.00				
	04/21/03			138.00	0.00				
	07/19/04			138.32	0.00				
	01/18/05			138.20	0.00				
	07/12/05			139.93	0.00				
MW-7	06/13/91	34.93	100.86	65.93	0.00	51 - 60	49 - 60	0 - 49	
	07/09/91	35.05	1	65.81	0.00				
	08/01/91	35.76	1	65.10	0.00				
	08/29/91	37.28		63.58	0.00				
	09/11/91	36.71		64.15	0.00				
	10/08/91	36.59		64.27	0.00				
	11/08/91	36.31		64.55	0.00				
	12/11/91	36.55	4	63.31	0.00	4			
	01/13/92	37.03		63.83	0.00				
	02/11/92	36.20		64.66	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)	,	Interval	Interval	Grout	
				Ź				Interval	
MW-7	03/11/92		100.86	66.35	0.00	51 - 60	49 - 60	0 - 49	
	04/13/92	33.85		67.01	0.00				
	05/15/92			67.82	0.00				
	06/15/92			65.33	0.00				
	07/16/92			65.44	0.00				
	08/18/92			65.83	0.00				
	09/18/92			65.34	0.00				
	12/08/92			66.50	0.00				
	03/10/93			70.65	0.00				
	06/04/93			71.53	0.00				
	10/14/93			68.63	0.00				
	04/11/94			71.99	0.00				
	10/19/94			69.67	0.00				
	04/11/95			78.37	0.00				
	03/06/96			79.42	0.00				
	10/14/96		101.03						Top of casing elevations re-surveyed.
	04/09/97			80.36	0.00				
	10/29/97			76.32	0.00				
	04/07/98			84.07	0.00				
	10/07/98			81.57	0.00				
	04/07/99			85.76	0.00				
	10/19/99			82.24	0.00				
	04/26/00		144.72	87.58	0.00				
	10/30/00		144.72		0.00				Top of casing elevations re-surveyed.
	02/01/01			128.55	0.00				
	04/23/01			126.60 125.19	0.00				
	07/23/01			123.19	0.00				
	10/23/01				0.00				Top of easing elevations were recommended for EDE
	01/21/02	16.30	147.37	131.07	0.00				Top of casing elevations were resurveyed for EDF compliance.
	04/25/02	16.27		131.10	0.00				
	07/22/02			129.56					
	10/22/02	-		128.47	0.00	1			
	01/27/03	15.20		132.17	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
Date	msl)		msl)		Interval	Interval	Grout	
							Interval	
		147.37			51 - 60	49 - 60	0 - 49	
		4						
09/09/05	14.86		132.51	0.00				
06/12/01	22.60	101.52	60.05	0.00	40 50	47.5 50	0 47.5	
					49 - 39	47.3 - 39	0 - 47.3	
		4						
		4						
		4						
12/11/91			66.54					
01/13/92	34.34	1	67.19	0.00				
02/11/92			66.99					
03/11/92			69.11					
04/13/92		4						
					ļ			
		4			4			
		4			4			
		4			4			
					1			
					4			Top of casing elevation re-surveyed.
	Date  04/21/03 07/21/03 01/20/04 07/19/04 01/18/05 07/12/05 09/09/05  06/13/91 08/01/91 08/29/91 10/08/91 11/08/91 11/08/91 11/08/91 02/11/92 03/11/92 04/13/92 05/15/92 06/15/92 07/16/92 08/18/92 12/08/92 12/08/92 12/08/93 10/14/93 04/11/94 10/19/94 04/11/95 03/06/96	Date         msl)           04/21/03         14.92           07/21/03         16.27           01/20/04         14.37           07/19/04         17.90           01/18/05         12.07           07/12/05         13.00           09/09/05         14.86           06/13/91         32.68           07/09/91         32.81           08/01/91         33.26           08/29/91         34.06           09/11/91         34.70           10/08/91         37.63           11/08/91         35.73           12/11/91         34.99           01/13/92         34.34           02/11/92         34.54           03/11/92         32.42           04/13/92         30.46           05/15/92         30.80           06/15/92         31.82           07/16/92         33.01           08/18/92         32.90           09/18/92         33.07           03/10/93         26.87           06/04/93         25.39           10/19/94         15.56           04/11/94         26.70           10/19/94         15.56	Date       msl)         04/21/03       14.92         07/21/03       16.27         01/20/04       14.37         07/19/04       17.90         01/18/05       12.07         07/12/05       13.00         09/09/05       14.86         06/13/91       32.68         07/09/91       32.81         08/01/91       33.26         08/29/91       34.06         09/11/91       34.70         10/08/91       37.63         11/08/91       35.73         12/11/91       34.99         01/13/92       34.34         02/11/92       34.54         03/11/92       32.42         04/13/92       30.46         05/15/92       30.80         06/15/92       31.82         07/16/92       33.01         08/18/92       32.90         09/18/92       33.60         12/08/92       33.07         03/10/93       26.87         06/04/93       25.39         10/14/93       29.90         04/11/94       26.70         10/19/94       15.56         04/11/95       19.87	Date         msl)         msl)           04/21/03         14.92         147.37         132.45           07/21/03         16.27         131.10           01/20/04         14.37         133.00           07/19/04         17.90         129.47           01/18/05         12.07         135.30           07/12/05         13.00         134.37           09/09/05         14.86         132.51           06/13/91         32.68         101.53         68.85           07/09/91         32.81         68.72           08/01/91         33.26         68.27           08/29/91         34.06         67.47           09/11/91         34.70         66.83           10/08/91         37.63         63.90           11/08/91         35.73         65.80           01/13/92         34.34         67.19           02/11/92         34.54         66.99           03/11/92         32.42         69.11           04/13/92         30.46         71.07           05/15/92         30.80         70.73           06/15/92         31.82         69.71           07/16/92         33.01         68.52	Date   msl   msl   msl   msl	Date   msl   msl	Date   msl)	Date   msl   msl

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)	, ,	Interval	Interval	Grout	
								Interval	
MW-8	04/10/97	19.06	101.42		0.00	49 - 59	47.5 - 59	0 - 47.5	
	10/29/97	23.91		77.51	0.00				
	04/07/98			86.27	0.00				
	10/07/98			82.40	0.00				
	04/07/99			87.03	0.00				
	10/19/99		4	82.02	0.00				
	04/26/00			87.64	0.00				
	10/30/00				0.00				Top of casing elevation re-surveyed.
	02/01/01	16.78		128.07	0.00				
	04/23/01	17.25		127.60	0.00				
	07/23/01	19.18	4		0.00				
	10/23/01	21.80		123.05	0.00				
	01/21/02	14.21	147.50	133.29	0.00				Top of casing elevations were surveyed for EDF compliance.
	04/25/02	15.82	ł	131.68	0.00				compnance.
	07/22/02	15.50		132.00	0.00				
	10/22/02	18.70		128.80	0.00				
	01/27/03	14.85		132.65	0.00				
	04/21/03	14.80		132.70	0.00				
	07/21/03			131.20	0.00				
	01/20/04		1	133.19	0.00				
	07/19/04		1	131.85	0.00	4			
	01/18/05			134.85	0.00				
	•							•	
MW-9	10/14/96	16.40	100.29	83.89	0.00	8 - 26	7 - 26	0 - 7	
	04/10/97	12.98		87.31	0.00				
	10/29/97	16.06		84.23	0.00				
	04/07/98	10.31		89.98	0.00				
	10/07/98	14.48	1	85.81	0.00				
	04/07/99	10.90		89.39	0.00				
	10/19/99	14.65		82.08	0.00				
	04/26/00	11.51		88.78	0.00				
	10/30/00				0.00				Top of casing elevation surveyed.
	02/01/01	14.12		130.54	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample		DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)		Interval	Interval	Grout	
1 5 1 1 1 0	0.4/22/01	15.54	144.66	100.10	0.00	0.26	7.06	Interval	
MW-9	04/23/01	15.54			0.00		7 - 26	0 - 7	
	07/23/01	16.45		128.21	0.00				
	10/23/01 01/21/02	18.80		125.86 131.79	0.00				Top of accine almosticus was summered for EDE
	01/21/02	15.52	147.31	131./9	0.00				Top of casing elevations were surveyed for EDF compliance.
	04/25/02	14.64		132.67	0.00				
	07/22/02	17.55		129.76	0.00				
	10/22/02	16.00		131.31	0.00				
	01/27/03	13.64		133.67	0.00				
	04/21/03	13.75		133.56	0.00				
	07/21/03	14.60			0.00				
	01/20/04			134.19	0.00				
	07/19/04			132.95	0.00				
-	01/18/05	11.76		135.55	0.00				
MW-10	04/10/99	12.04	102.04	0.00	0.00	5 - 20	4.5 - 20	0 - 4.5	
141 44 -10	10/19/99		4	0.00	0.00	3 - 20	4.3 - 20	0 - 4.3	
	04/26/00			0.00	0.00	1			
	10/30/00			135.15	0.00				Top of casing elevation surveyed.
	02/01/01		4	134.03	0.00				of or thistage of the order of the
	04/23/01	13.92	4	131.48	0.00				
	07/23/01	14.75		130.65	0.00				
	10/23/01			128.19	0.00				
	01/21/02	13.00	148.05	135.05	0.00				Top of casing elevations were surveyed for EDF compliance.
	04/25/02	14.05	1	134.00	0.00				
	07/22/02	14.30		133.75	0.00				
	10/22/02	14.70		133.35	0.00				
	01/27/03	12.62		135.43	0.00				
	04/21/03	12.81		135.24	0.00				
	07/21/03	13.75		134.30	0.00				
	01/20/04			136.34	0.00				
	07/19/04			134.69	0.00				
	01/18/05	10.05		138.00	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)	` ′	msl)		Interval	Interval	Grout	
		,						Interval	
MW-10	07/12/05	11.60	148.05	136.45	0.00	5 - 20	4.5 - 20	0 - 4.5	
	09/09/05	12.76	]	135.29	0.00				
MW-11	05/08/00	18.21	101.74		0.00	15-35	13-35	0-13	
	06/07/00	19.05		82.69	0.00				
	10/30/00	23.70			0.00				Top of casing elevation surveyed.
	02/01/01	21.73		124.64	0.00				
	04/23/01	20.21	1	126.16	0.00				
	07/23/01	22.69		123.68	0.00				
	10/23/01	25.65		120.72	0.00				
	01/21/02	17.95	149.02	131.07	0.00				Top of casing elevations were surveyed for EDF
			1						compliance.
	04/25/02			131.67	0.00	-1			
	07/22/02	20.10		128.92	0.00	-1			
	10/22/02	21.91		127.11	0.00				
	01/27/03			131.70					
	04/21/03			132.66	0.00				
	07/21/03			130.94	0.00				
	01/20/04		-	132.75	0.00				
	07/19/04								
2.5777.42	0.5/0.0/0.0	20.55	101.15	00.40		10.00	T 0 20	1 0 0	<u></u>
MW-12	05/08/00						8 - 30	0 - 8	
	06/07/00 10/30/00			79.90 120.95					To a Consideration of the state
	02/01/01			120.95	0.00				Top of casing elevation surveyed.
	04/23/01	22.00		124.38					
	07/23/01	24.11		124.38	0.00				
	10/23/01	26.38		120.00	0.00				
	01/21/02	19.70			0.00				Top of casing elevations were surveyed for EDF
	01/21/02	19.70	147.03	127.33	0.00				compliance.
	04/25/02	18.91	1	130.12	0.00	1			
	07/22/02			127.82	0.00				
	10/22/02	23.98		125.05	0.00				
	01/27/03			130.28					

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
		msl)		msl)		Interval	Interval	Grout	
								Interval	
MW-12	04/21/03		149.03		0.00	10 - 30	8 - 30	0 - 8	
	07/21/03			129.32	0.00				
	01/20/04			130.60	0.00				
	07/19/04			130.64	0.00				
	01/18/05	16.94		132.09	0.00				
						•			
MW-13	05/08/00			79.21	0.00	10 - 30	8 - 30	0 - 8	
	06/07/00			78.78	0.00				
	10/30/00		147.32		0.00				Top of casing elevation surveyed.
	02/01/01	26.11	]	121.21	0.00				
	04/23/01	23.56		123.76	0.00				
	07/23/01			121.56					
	10/23/01	27.60		119.72	0.00				Monitoring well has been abandoned.
MW-14	05/08/00					10-30	8-30	0-8	
	06/07/00			79.05	0.00				
	10/30/00		144.96		0.00				Top of casing elevation surveyed.
	02/01/01			121.39	0.00				
	04/23/01			123.83	0.00				
	07/23/01			121.78					
	10/23/01	25.50	<u></u>	119.46	0.00				Monitoring well has been abandoned.
	_						•	•	
MW-15	05/08/00				0.00		7-25	0-7	
	06/07/00								
	10/30/00				0.00				Top of casing elevation surveyed.
	02/01/01			130.40					
	04/23/01			128.72	0.00				
	07/23/01			125.82	0.00	-1			
	10/23/01			123.27	0.00				
	01/21/02	14.80	148.09	133.29	0.00				Top of casing elevations were surveyed for EDF
			_						compliance.
	04/25/02			133.21	0.00				
	07/22/02			131.62	0.00				
	10/22/02	18.84	<u> </u>	129.25	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	, ,	DTW (Ft)	` '	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)		Interval	Interval	Grout	
								Interval	
MW-15	01/27/03		148.09		0.00	8-25	7-25	0-7	
	04/21/03	13.31		134.78	0.00				
	07/21/03			133.98	0.00				
	01/20/04		ļ	134.94	0.00				
	07/19/04		ļ	134.97	0.00				
	01/18/05			136.51	0.00				
	07/12/05	11.23		136.86	0.00			1	
NAVY 16	05/00/00	1405	1	1	0.00	0.25	7.05	0.7	T
MW-16	05/08/00 06/07/00			87.05	0.00		7-25	0-7	
	10/30/00				0.00				Ton of social alcostical summand
	02/01/01	18.77 18.17	4	128.91	0.00				Top of casing elevation surveyed.
	04/23/01	14.58	4	133.10					
	07/23/01			123.42	0.00	-			
	10/23/01		4	123.42	0.00	-			
	01/21/02		150.33		0.00				Top of casing elevations were surveyed for EDF
	01/21/02	14.11	130.33	130.22	0.00				compliance.
	04/25/02	13.66	1	136.67	0.00	1			compnance.
	07/22/02			132.73	0.00	1			
	10/22/02		4	131.58	0.00				
	01/27/03			137.36	0.00				
	04/21/03			136.35	0.00	1			
	07/21/03		4	135.67	0.00	-			
	01/20/04			137.95	0.00				
	07/19/04			136.92	0.00				
	01/18/05			138.95	0.00				
	07/12/05	11.38	1	138.95	0.00				
		•	•				-		
MW-17	05/08/00	7.80	103.65	95.85	0.00	8 - 25	7 - 25	0 - 7	
	06/07/00			95.14	0.00				
	10/30/00		4		0.00	-			Top of casing elevation surveyed.
	02/01/01			140.42	0.00	-			
	04/23/01			139.90					
	08/22/01	11.80		136.48	0.00			1	

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample Date	TOC (Ft, msl)	DTW (Ft)	GWE (Ft, msl)	Product (ft)	Screen Interval	Sand Pack Interval	Bentonite/ Grout	Notes
		,						Interval	
MW-17	10/23/01	13.15	148.28	135.13	0.00	8 - 25	7 - 25	0 - 7	
	01/21/02	7.10	150.93	143.83	0.00				Top of casing elevations were surveyed for EDF
									compliance.
	04/25/02	6.70		144.23	0.00				
	07/22/02								Well was inaccessible
	10/22/02	11.31		139.62	0.00				
	01/27/03	9.55		141.38	0.00				
	04/21/03								Well was inaccessible
	01/20/04								Well was inaccessible
	07/19/04								
	01/17/05								
	07/12/05	7.07		143.86	0.00				
	_					•			
MW-18	05/08/00		4		0.00	8 - 25	7 - 25	0 - 7	
	06/07/00			88.11	0.00				
	10/30/00		144.14		0.00				Top of casing elevation surveyed.
	02/01/01	13.91		130.23					
	04/23/01	13.30		130.84	0.00	-			
	07/23/01	14.71		129.43	0.00	-			
	10/23/01			125.99		-			
	01/21/02	12.15	146.79	134.64	0.00				Top of casing elevations were surveyed for EDF
									compliance.
	04/25/02	12.29		134.50					
	07/22/02	13.76		133.03	0.00				
	10/22/02			132.03	0.00				
	01/27/03		ļ	135.38	0.00				
	04/21/03			135.21	0.00				
	07/21/03	12.71		134.08	0.00				
	01/20/04		4	135.60		-			
	07/19/04			134.12	0.00	-			
	01/17/05	10.91		135.88	0.00		ļ	<u> </u>	

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)	l , , ,	msl)		Interval	Interval	Grout	
								Interval	
MW-19	05/08/00				0.00	8 - 25	7 - 25	0 - 7	
	06/07/00			90.80	0.00				
	10/30/00		145.18		0.00				Top of casing elevation surveyed.
	02/01/01			132.53	0.00				
	04/23/01			134.63	0.00				
	07/23/01			132.91	0.00				
	10/23/01			131.26	0.00				
	01/21/02	9.44	147.83	138.39	0.00				Top of casing elevations were surveyed for EDF
	0.4/2.7/0.2	0.61		100.00					compliance.
	04/25/02		4	138.22	0.00				
	07/22/02			137.18	0.00				
	10/22/02 01/27/03			136.17 138.23	0.00				
	04/21/03			138.23	0.00				
	07/21/03			138.28	0.00				
	01/20/04			138.63	0.00				
	07/19/04			137.15	0.00				
	01/17/05			138.50					
	01/1//02	7.55	<u>l</u>	130.00	0.00	<u> </u>	1	1	
MW-20	06/07/00	9.47	103.13	93.66	0.00	10-25	8-25	6-8	
	10/30/00		147.48		0.00				Top of casing elevation surveyed.
	2/15/0112	11.42	1	136.06	0.00				
	4/23/0113								
	07/23/01	12.37		135.11	0.00				
	10/23/01			134.03	0.00				
	01/21/02	9.68	150.13	140.45	0.00				Top of casing elevations were surveyed for EDF
									compliance.
	04/25/02								Well was inaccessible
	07/22/02			138.72	0.00	4			
	10/22/02			138.15	0.00				
	01/27/03			139.35	0.00				
	04/21/03			140.26	0.00	4			
	07/21/03			137.97	0.00	4			
	01/20/04	8.94		141.19	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)	` /	msl)	,	Interval	Interval	Grout	
		,		ŕ				Interval	
MW-20	07/19/04		150.13	139.35	0.00	10-25	8-25	6-8	
	01/17/05	8.98		141.15	0.00				
V-1	06/13/91	21.89	102.53			15.5 - 25.5	13.5 - 25.5	0 - 13.5	
	07/09/91	21.91		80.62	0.00	4			
	08/01/91	21.34		81.19	0.00				
	08/29/91	21.10		81.43	0.00				
	09/11/91			81.28	0.00				
	10/08/91	22.88		79.65	0.00				
	11/08/91	22.15		80.38	0.00				
	12/11/91								
	01/13/92	21.28		81.25	0.00				
	02/11/92	18.75		83.78	0.00				
	03/11/92	13.54		88.99	0.00				
	04/13/92	14.52		88.01	0.00				
	05/15/92	15.18		87.35	0.00				
	06/15/92	16.29		86.24	0.00				
	07/16/92	17.22	102.53		0.00				
	08/18/92	17.08		85.45	0.00				
	09/18/92	18.25		84.28	0.00				
	12/08/92	17.80		84.73	0.00				
	03/10/93	15.59		86.94	0.00				
	06/04/93	14.97		87.56	0.00				
	10/14/93	14.66		87.87	0.00				
	04/11/94			88.53	0.00	ļ			
	10/19/94			88.61	0.00				
	04/11/95			93.25	0.00				
	03/06/96		100 71	92.81	0.00				
	10/14/96		102.51		0.00				Top of casing elevations were surveyed.
	04/09/97	10.48		92.03	0.00				
	10/29/97	13.96		88.57	0.02				
	04/07/98			94.50					
	10/07/98			91.41	0.00				
	04/07/99	8.15		94.36	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	` '	DTW (Ft)	` ′	Product (ft)		Sand Pack		Notes
	Date	msl)		msl)		Interval	Interval	Grout Interval	
V-1	10/19/99	11.49	102.51	91.02	0.00	15.5 - 25.5	13.5 - 25.5	0 - 13.5	
	04/26/00	8.64	1	93.87	0.00				
	10/30/00	11.85	146.85	135.00	0.00				Top of casing elevations were surveyed.
	02/26/01	12.55		134.30	0.00				
	04/23/01	13.14		133.71	0.00				
	07/23/01	13.73	-	133.12	0.00				
	10/23/01	14.85		132.00	0.00				
	01/21/02	11.70	149.50	137.80	0.00				Top of casing elevations were surveyed for EDF compliance.
	04/25/02	11.65		137.85	0.00				
	07/22/02	12.52		136.98	0.00				
	10/22/02	12.90		136.60	0.00				
	01/27/03	11.43	]	138.07	0.00				
	04/21/03	11.44	-1	138.06	0.00				
	07/21/03		-	137.42	0.00				
	01/20/04		-	138.96	0.00				
	07/19/04			137.58	0.00				
	01/17/05			139.29	0.00				
	07/12/05	9.96		139.54	0.00				
	1	T	1	1		1	1	T	
V-2	06/13/91		101.13			8 - 23	7 - 23	0 - 7	
	07/09/91		-						
	08/01/91		-						
	08/29/91								
	09/11/91								
	10/08/91								
	11/08/91								
	12/11/91			00.74					
	01/13/92	18.39	-1	82.74	0.00	4			
	02/11/92	21.16	-	79.97	0.00	4			
	03/11/92	16.86	-	84.27	0.00				
	04/13/92	17.03	-	84.10					
	05/15/92	17.78		83.35	0.00				
	06/15/92	21.44	<u> </u>	79.69	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)	, ,	Interval	Interval	Grout	
		,						Interval	
V-2	07/16/92		101.13			8 - 23	7 - 23	0 - 7	
	08/18/92					1			
	09/18/92								
	12/08/92	19.41		81.72	0.00				
	03/10/93	13.62		87.51	0.00				
	06/04/93	12.98		88.15	0.00				
	10/14/93								
	04/11/94			81.02	0.00				
	10/19/94								
	04/11/95			88.99	0.00				
	03/06/96			88.12	0.00				
	10/14/96		100.82		0.00				
	04/09/97	13.46		87.36	0.00				
	10/29/97	17.24		83.58	0.00				
	04/07/98			94.50	0.00				
	10/07/98		]	87.14	0.00				
	04/07/99		]	90.26	0.00				
	10/19/99		]	86.86	0.00				
	04/26/00			91.51	0.00				
	10/30/00		4		0.00				Top of casing elevations were surveyed.
	02/26/01	10.36	4	133.49	0.00	4			
	04/23/01		]	128.75	0.00				
	08/22/01	15.48		128.37	0.00				Well has been switched to a SVE (soil vapor
									extraction) well.
							_		
DW-1	06/13/91				0.00		61 - 180	0 - 61	Well has been abandoned.
	07/09/91			64.82	0.00				
	08/01/91			10.38	0.00	4			
	08/29/91	50.13		52.51	0.00	4			
	09/11/91	39.72		62.92	0.00	4			
	10/08/91	39.31		63.33	0.00	4			
	11/09/91	38.90	4	63.74	0.00				
	12/11/91	39.96		62.68	0.00				
	12/08/92	37.75		64.89	0.00				

Table 7. Water Level Data/Well Construction Details - Redwood Oil Bulk Plant, 455 Yolanda Ave. Santa Rosa, CA

Well ID	Sample	TOC (Ft,	DTW (Ft)	GWE (Ft,	Product (ft)	Screen	Sand Pack	Bentonite/	Notes
	Date	msl)		msl)		Interval	Interval	Grout	
								Interval	
DW-1	03/10/93	32.60	102.64	70.04	0.00	140 - 180	61 - 180	0 - 61	
	06/04/93	32.35		70.29	0.00				
	10/14/93								
DW-2	03/09/74					94 - 134	unknown	0 - 20	Well has been abandoned.
	10/17/95								
	10/21/96								
	04/10/97								
	10/30/97								
	04/08/98		1			1			
	10/07/98		]						
	04/07/99		]						
	08/30/99	23.23	]		0.48	]			

# **EXPLANATION:**

**DTW** = Depth to water

**ft** =feet

msl = mean sea level

TOC = Top of casing elevation GWE = Ground water elevation

— = Not applicable

Table 8. Hydrocarbon and MTBE Removal - Redwood Oil Company Bulk Plant, 455 Yolanda Ave., Santa Rosa, CA

1st qtr 05	341,069	430	0.56	530	0.60	Lab indicated no TPH(D) or TPH(G) present.  Concentration is from light Oil in the C12-C36 range.
4th qtr '04	194,170	2,000	1.47	190	0.14	
3rd qtr '04	86,505	410	0.13	600	0.2	
2nd qtr '04	80,599	540		760		
1st qtr '04	157,526					
4th qtr '03	68,947	790		110		
3rd qtr '03	295,358			,		
2nd qtr '03	471,556					
1st qtr '03	413,190	950			4.85	
4th qtr '02	255,724	887	0.86			
3rd qtr '02	208,672	1,130		,		
2nd qtr '02	390,485	1,242	0.49	,		
4th qtr '01 1st qtr '02	192,067 369,942	3,100 1,277	2.48 1.79			
3rd qtr '01	158,860	5,850			2.83	
2nd qtr '01	46,786	,			0.74	
<b>a</b> 1	10-22					
Quarter	Pumped	(ug/L)	Removal (kg)	MTBE	(kg)	notes
	Gallons	(TPH[D] + TPH[G])	Hydrocarbon	Influent	Removal	
		Concentratinon			MTBE	
		Influent Hydrocarbon				

LABORATORY ANALYTICAL R	APPENDIX C REPORTS AND CHAIN	OF CUSTODY RECORDS

3334 Victor Court • Santa Clara, CA 95054 • (408) 588-0200 • Fax (408) 588-0201

Jim Green

Certificate ID: 44305 - 7/14/2005 5:52:48 PM

ECM Group

290 W. Channel Rd. Benicia, CA 94510

Order Number: 44305

Date Received: 7/8/2005 2:26:53 PM

Project Name: Windsor / Yolanda

Project Number: 98-507-91

#### Certificate of Analysis - Final Report

On July 08, 2005, samples were received under chain of custody for analysis. Entech analyzes samples "as received" unless otherwise noted. The following results are included:

Matrix

<u>Test</u>

Comments

Liquid

EPA 8260B - GC/MS TPH as Gasoline by GC/MS

TPH-Extractable w/SGCU

Entech Analytical Labs, Inc. is certified for environmental analyses by the State of California (#2346). If you have any questions regarding this report, please call us at 408-588-0200 ext. 225.

Sincerely,

Laurie Glantz-Murphy Laboratory Director

3334 Victor Court , Santa Clara, CA 95054

Phone: (408) 588-0200

Fax: (408) 588-0201

ECM Group 290 W. Channel Rd. Benicia, CA 94510 Attn: Jim Green

Project ID: 98-507-91 Date Received: 7/8/2005

Sample Collected by: Client

#### Certificate of Analysis - Data Report

Lab #: 44305-00	Sample ID: Influent			]	<b>Matrix:</b> Liq	uid Sample I	Date: 7/6/2005	1:30 PM
EPA 3510C EPA 80 Parameter	15 MOD.(Extractable with Silica Result Qua		nup) Detection Limit	Units	Prep Date	Prep Batch	TPH-Extr Analysis Date	actable-SGCU QC Batch
TPH as Diesel  Not a typical Die	350 esel pattern(C10-C34).	1	50	μg/L	7/8/2005	DW050708S	7/11/2005	DW050708S
Surrogate o-Terphenyl	Surrogate Recovery 91.2		Limits (%) - 137				Analyzed by: JHsia Reviewed by: dba	ng

EPA 5030B EPA 8260B EPA	A 624							8260Petroleum
Parameter	Result Qual	DF	<b>Detection Limit</b>	Units	Prep Date	Prep Batch	<b>Analysis Date</b>	QC Batch
Benzene	12	5	2.5	μg/L	N/A	N/A	7/13/2005	WMS1050713
Toluene	ND	5	2.5	μg/L	N/A	N/A	7/13/2005	WMS1050713
	ND	5	2.5	μg/L	N/A	N/A	7/13/2005	WMS1050713
Ethyl Benzene	2.7	5	2.5	μg/L	N/A	N/A	7/13/2005	WMS1050713
Xylenes, Total	360	5	5.0	μg/L	N/A	N/A	7/13/2005	WMS1050713
Methyl-t-butyl Ether		5	25	μg/L	N/A	N/A	7/13/2005	WMS1050713
tert-Butyl Ethyl Ether	ND	5	50	μg/L μg/L	N/A	N/A	7/13/2005	WMS1050713
tert-Butanol (TBA)	530	3			N/A	N/A	7/13/2005	WMS1050713
Diisopropyl Ether	ND	5	25 25	μg/L		N/A	7/13/2005	WMS1050713
tert-Amyl Methyl Ether	ND	5	25	μg/L	IN/A	1N/A	771312003	

Surrogate	Surrogate Recovery	Control Limits (%)	Analyzed by: XBian
4-Bromofluorobenzene	99.0	70 - 125	Reviewed by: bdhabalia
Dibromofluoromethane	106	70 - 125	
Toluene-d8	97.3	70 - 125	

EPA 5030B GC-MS								TPH as Gasoline - GC-MS		
Parameter	Result Qu	ıal	DF		<b>Detection Limit</b>	Units	Prep Date	Prep Batch	Analysis Date	QC Batch
TPH as Gasoline	270		5		250	μg/L	N/A	N/A	7/13/2005	WMS1050713
Surrogate	Surrogate Recovery	(	Control Limits (%)						Analyzed by: XBia	n
4-Bromofluorobenzene	105		70	-	125				Reviewed by: bdha	balia
Dibromofluoromethane	97.4		70	-	125					
Toluene-d8	95.0		70	-	125					

3334 Victor Court , Santa Clara, CA 95054

Phone: (408) 588-0200

Fax: (408) 588-0201

ECM Group 290 W. Channel Rd. Benicia, CA 94510 Attn: Jim Green

Project ID: 98-507-91 Date Received: 7/8/2005

Sample Collected by: Client

#### Certificate of Analysis - Data Report

<b>Lab</b> #: 44305-002	Sample ID: Mid			]	Matrix: Liq	uid Sample I	Date: 7/6/2005	1:40 PM
EPA 3510C EPA 8015	5 MOD.(Extractable with Silica Result Qual		up) Detection Limit	Units	Prep Date	Prep Batch	TPH-Extr Analysis Date	actable-SGCU QC Batch
TPH as Diesel	ND	1	50	μg/L	7/8/2005	DW050708S	7/11/2005	DW050708S
Surrogate o-Terphenyl	Surrogate Recovery 82.4		<b>Limits (%)</b> - 137				Analyzed by: JHsia Reviewed by: dba	ng

EPA 5030B EPA 8260B EF	PA 624		D ( ) T ( )	#1:4	Dwan Data	Prep Batch	Analysis Date	8260Petroleum OC Batch
Parameter	Result Qual	DF	Detection Limit	Units	Prep Date			
Benzene	ND	1	0.50	μg/L	N/A	N/A	7/12/2005	WMS1050712
Toluene	ND	1	0.50	μg/L	N/A	N/A	7/12/2005	WMS1050712
Ethyl Benzene	ND	1	0.50	μg/L	N/A	N/A	7/12/2005	WMS1050712
<b>J</b>	ND	1	0.50	μg/L	N/A	N/A	7/12/2005	WMS1050712
Xylenes, Total	ND ND	1	1.0	μg/L	N/A	N/A	7/12/2005	WMS1050712
Methyl-t-butyl Ether		1	5.0	μg/L	N/A	N/A	7/12/2005	WMS1050712
tert-Butyl Ethyl Ether	ND					N/A	7/12/2005	WMS1050712
tert-Butanol (TBA)	11	1	10	μg/L	N/A			
Diisopropyl Ether	ND	1	5.0	μg/L	N/A	N/A	7/12/2005	WMS1050712
tert-Amyl Methyl Ether	ND	1	5.0	μg/L	N/A	N/A	7/12/2005	WMS1050712
	C	C 4 1	Limits (0/s)	Analyzed by: XBian				an

Surrogate	Surrogate Recovery	Control Limits (%)	Analyzed by: XBian		
4-Bromofluorobenzene	99.8	70 - 125	Reviewed by: BDhaba		
Dibromofluoromethane	110	70 - 125			
Toluene-d8	98.4	70 - 125			

EPA 5030B GC-MS							TPH as Gasoline - GC-MS	
Parameter	Result Qua	l DF	<b>Detection Limit</b>	Units	Prep Date	Prep Batch	Analysis Date	QC Batch
TPH as Gasoline	ND	1	50	μg/L	N/A	N/A	7/12/2005	WMS1050712
Surrogate	Surrogate Recovery	Contro	Limits (%)				Analyzed by: XBia	n
4-Bromofluorobenzene	106	70	- 125				Reviewed by: BDh	abalia
Dibromofluoromethane	101	70	- 125					
Toluene-d8	96.1	70	- 125					

3334 Victor Court, Santa Clara, CA 95054 Phone: (408) 588-0200 Fax: (408) 588-0201

Method Blank - Liquid - EPA 8015 MOD.(Extractable with Silica Gel Cleanup) - TPH-Extractable-SGCU

QC/Prep Batch ID: DW050708S

Validated by: dba - 07/11/05

QC/Prep Date: 7/8/2005

Surrogate for Blank % Recovery Control Limits o-Terphenyl 72.8 16 - 137

3334 Victor Court , Santa Clara, CA 95054

Phone: (408) 588-0200 Fax: (408) 588-0201

Laboratory Control Sample / Duplicate - Liquid - EPA 8015 MOD.(Extractable with Silica Gel Cleanup) - TPH-

**Extractable-SGCU** 

QC/Prep Batch ID: DW050708S

Reviewed by: dba - 07/11/05

QC/Prep Date: 7/8/2005

LCS	
_	

LCS Parameter	Method Blank	Spike Amt	SpikeResult	Units	% Recovery	Recovery Limits
TPH as Diesel	<50	1000	657	μg/L	65.7	35 - 109
TPH as Motor Oil	<250	1000	827	μg/L	82.7	30 - 132

**Control Limits** % Recovery Surrogate 81.3 16 - 137 o-Terphenyl

LCSD

Parameter	Method Blank	Spike Amt	SpikeResult	Units	% Recovery	RPD	RPD Limits	Recovery Limits
TPH as Diesel	<50	1000	716	μg/L	71.6	8.6	25.0	35 - 109
TPH as Motor Oil	<250	1000	939	μg/L	93.9	13	25.0	30 - 132

**Control Limits** % Recovery Surrogate 16 - 137 85.8 o-Terphenyl

3334 Victor Court , Santa Clara, CA 95054

Phone: (408) 588-0200 Fax: (408)

Fax: (408) 588-0201

Validated by: BDhabalia - 07/13/05

Method Blank - Liquid - EPA 8260B - 8260Petroleum

QC Batch ID: WMS1050712 Validated by: BDhabalia - 07/13/05

QC Batch Analysis Date: 7/12/2005

Parameter	Result	DF	PQLR	Units
Benzene	ND	1	0.50	μg/L
Diisopropyl Ether	ND	1	5.0	μg/L
Ethyl Benzene	ND	1	0.50	μg/L
Methyl-t-butyl Ether	ND	1	1.0	μg/L
tert-Amyl Methyl Ether	ND	1	5.0	μg/L
tert-Butanol (TBA)	ND	1	10	μg/L
tert-Butyl Ethyl Ether	ND	1	5.0	μg/L
Toluene	ND	1	0.50	μg/L
Xylenes, Total	ND	1	0.50	μg/L

Surrogate for Blank% RecoveryControl Limits4-Bromofluorobenzene96.670 - 125Dibromofluoromethane99.870 - 125Toluene-d898.170 - 125

Method Blank - Liquid - GC-MS - TPH as Gasoline - GC-MS

QC Batch ID: WMS1050712

QC Batch Analysis Date: 7/12/2005

ParameterResultDFPQLRUnitsTPH as GasolineND150µg/L

Surrogate for Blank% RecoveryControl Limits4-Bromofluorobenzene10270- 125Dibromofluoromethane91.370- 125Toluene-d895.870- 125

Phone: (408) 588-0200 Fax: (408) 588-0201 3334 Victor Court , Santa Clara, CA 95054

Laboratory Control Sample / Duplicate - Liquid - EPA 8260B - 8260Petroleum

Reviewed by: BDhabalia - 07/13/05 QC Batch ID: WMS1050712

QC Batch ID Analysis Date: 7/12/2005

L	C	S	
_			

LCS Parameter	Method B	lank Sp	ike Amt	SpikeResult	Units	% Recovery	Recovery Limits
Benzene	<0.50		20	21.2	μg/L	106	70 - 130
Methyl-t-butyl Ether	<1.0		20	22.5	μg/L	112	70 - 130
Toluene	<0.50		20	20.3	μg/L	102	70 - 130
Surrogate	% Recovery	Contro	ol Limits				
4-Bromofluorobenzene	99.7	70	- 125				
Dibromofluoromethane	103	70	- 125				
Toluene-d8	96.2	70	- 125				

LCSD Parameter Benzene Methyl-t-butyl Ether Toluene	Method B <0.50 <1.0 <0.50	lank Spike Amt 20 20 20	<b>SpikeResult</b> 19.3 21.7 18.6	<b>Units</b> μg/L μg/L μg/L	% Recovery 96.5 108 93.0	RPD 9.4 3.6 8.7	25.0 25.0 25.0 25.0	Recovery Limits 70 - 130 70 - 130 70 - 130	
Surrogate	% Recovery	<b>Control Limits</b>							
4-Bromofluorobenzene	99.4	70 - 125							
Dibromofluoromethane	103	70 - 125							
Toluene-d8	95.3	70 - 125							

Laboratory Control Sample / Duplicate - Liquid - GC-MS - TPH as Gasoline - GC-MS

Reviewed by: BDhabalia - 07/13/05 QC Batch ID: WMS1050712

QC Batch ID Analysis Date: 7/12/2005

#### **LCS**

Parameter TPH as Gasoline	Method Bl <25	lank Spike Amt 120	SpikeResult 112	Units μg/L	% Recovery 89.6			Recovery Limits 65 - 135	
Surrogate 4-Bromofluorobenzene Dibromofluoromethane Toluene-d8	% Recovery 102 91 96.1	Control Limits 70 - 125 70 - 125 70 - 125							
LCSD Parameter TPH as Gasoline	Method B <25	lank Spike Amt 120	SpikeResult 106	<b>Units</b> μg/L	% Recovery 85.0	RPD 0.0	RPD Limits 25.0	Recovery Limits 65 - 135	
Surrogate	% Recovery	<b>Control Limits</b>							
4-Bromofluorobenzene	103	70 - 125							
Dibromofluoromethane	91.8	70 - 125							
Toluene-d8	95.8	70 - 125							

**Recovery Limits** 

3334 Victor Court , Santa Clara, CA 95054

Phone: (408) 588-0200 Fax: (408) 588-0201

Matrix Spike / Matrix Spike Duplicate - Liquid - EPA 8260B - 8260Petroleum

QC Batch ID: WMS1050712

Reviewed by: BDhabalia - 07/13/05

QC Batch ID Analysis Date: 7/12/2005

	_	
м	c	
w	Э	

Sample Spiked: 44303-001

IVIO		Campio - pi						
Barranatan		Sample Result	Spike Amount	Spike Result	Units	Analysis Date	% Recovery	Recovery Limits
Parameter		ND	20	19.8	μg/L	7/12/2005	99.0	70 - 130
Benzene		1.60	20	22.8	μg/L	7/12/2005	106	70 - 130
Methyl-t-butyl Ether		ND	20	19.9	μg/L	7/12/2005	99.5	70 - 130
Toluene		ND	20	10.0	M9, -	.,,=,=,=,		
Surrogate	% Recovery	Control Li	imits					
4-Bromofluorobenzene	96.8	70 - 1	.25					
Dibromofluoromethane	103	70 - 1	25					
Toluene-d8	99.1	70 - 1	125					

#### **MSD**

Sample Spiked: 44303-001

Parameter	Sample Result	Spike Amount	Spike Result	Units	Analysis Date	% Recovery	RPD	RPD Limits	Recovery Limits
Benzene	ND	20	20.2	μg/L	7/12/2005	101	2.0	25.0	70 - 130
Methyl-t-butyl Ether	1.60	20	23.0	μg/L	7/12/2005	107	0.94	25.0	70 - 130
Toluene	ND	20	20.8	μg/L	7/12/2005	104	4.4	25.0	70 - 130

Surrogate	% Recovery	Control Limits			
4-Bromofluorobenzene	92.6	70	-	125	
Dibromofluoromethane	103	70	-	125	
Toluene-d8	102	70	-	125	

3334 Victor Court , Santa Clara, CA 95054 Phone: (408) 588-0200 Fax: (408) 588-0201

Method Blank - Liquid - EPA 8260B - 8260Petroleum

QC Batch ID: WMS1050713 Validated by: bdhabalia - 07/14/05

QC Batch Analysis Date: 7/13/2005

Result	DF	PQLR	Units
ND	1	0.50	μg/L
ND	1	5.0	μg/L
ND	1	0.50	μg/L
ND	1	1.0	μg/L
ND	1	5.0	μg/L
ND	1	10	μg/L
ND	1	5.0	μg/L
ND	1	0.50	μg/L
ND	1	0.50	μg/L
	ND ND ND ND ND ND	ND 1	ND 1 0.50 ND 1 5.0 ND 1 0.50 ND 1 1.0 ND 1 5.0 ND 1 5.0 ND 1 5.0 ND 1 5.0 ND 1 0.50 ND 1 0.50

Surrogate for Blank% RecoveryControl Limits4-Bromofluorobenzene97.470-125Dibromofluoromethane10070-125Toluene-d897.770-125

Method Blank - Liquid - GC-MS - TPH as Gasoline - GC-MS

QC Batch ID: WMS1050713 Validated by: bdhabalia - 07/14/05

QC Batch Analysis Date: 7/13/2005

ParameterResultDFPQLRUnitsTPH as GasolineND150 $\mu g/L$ 

Surrogate for Blank
4-Bromofluorobenzene
Dibromofluoromethane
Toluene-d8

% Recovery
103
70 - 125
70 - 125
70 - 125

Phone: (408) 588-0200 Fax: (408) 588-0201 3334 Victor Court , Santa Clara, CA 95054

Laboratory Control Sample / Duplicate - Liquid - EPA 8260B - 8260Petroleum

Reviewed by: bdhabalia - 07/14/05 QC Batch ID: WMS1050713

Units

μg/L

μg/L

μg/L

% Recovery 104

116

98.0

QC Batch ID Analysis Date: 7/13/2005

Parameter	Method Blank	Spike Amt	SpikeResult
Benzene	<0.50	20	20.9
Methyl-t-butyl Ether	<1.0	20	23.2
Toluene	<0.50	20	19.6
Surrogate	% Recovery Co	ntrol Limits	

70 - 125 100 4-Bromofluorobenzene 104 70 - 125 Dibromofluoromethane 70 - 125 Toluene-d8 94.4

LC	;;	D	

Parameter	Method Blank	Spike Amt	SpikeResult	Units	% Recovery	RPD	RPD Limits	Recovery Limits	
Benzene	< 0.50	20	21.4	μg/L	107	2.4	25.0	70 - 130	
Methyl-t-butyl Ether	<1.0	20	23.6	μg/L	118	1.7	25.0	70 - 130	
Toluene	<0.50	20	20.5	μg/L	102	4.5	25.0	70 - 130	
Surrogate 4-Bromofluorobenzene	70 11000 1019	ontrol Limits 70 - 125							

70 - 125 104 Dibromofluoromethane 70 - 125 94 Toluene-d8

Laboratory Control Sample / Duplicate - Liquid - GC-MS - TPH as Gasoline - GC-MS

Reviewed by: bdhabalia - 07/14/05 QC Batch ID: WMS1050713

QC Batch ID Analysis Date: 7/13/2005

LCS

Parameter TPH as Gasoline	Method B <25	lank Spike Amt 120	SpikeResult 115	<b>Units</b> μg/L	% Recovery 91.9	Recovery Limits 65 - 135
Surrogate	% Recovery	Control Limits				
4-Bromofluorobenzene	104	70 - 125				
Dibromofluoromethane	91.8	70 - 125				
Toluene-d8	94	70 - 125				

LCSD	ı
Parame	eter
TOLL	o 1:

Parameter TPH as Gasoline	Method B <25	lank Spike Amt 120	SpikeResult 111	<b>Units</b> μg/L	% Recovery 88.5	RPD 3.8	RPD Limits 25.0	Recovery Limits 65 - 135
Surrogate	% Recovery	<b>Control Limits</b>						
4-Bromofluorobenzene	102	70 - 125						
Dibromofluoromethane	90.9	70 - 125						
Toluene-d8	93.8	70 - 125						

**Recovery Limits** 

70 - 130

70 - 130

70 - 130

#### Chain of Custody / Analysis Request Remarks General Chemistry Quote No.: Phone: State: GC Methods Company: Billing Address: (If Different) Invoice to: (If Different) GC/MS Methods Project No.: 98-507-9 YOLANDA Purchase Order No.: Project Location: 2 Entech Analytical Labs, Inc. 1 Day 3 Day 5 Day Zip Code: 767-751-0653 Phone No.: 767-751-0655 Turn Around Time 1 2 Day 1 4 Day 1 10 Day (408) 588-0201 - Fax Sample (408) 588-0200 Email Address: Date Lab. No. Field Org. Code: 00 F.O. BOK 802 Santa Clara, CA 95054 3334 Victor Court Client ID / Field Point ECM GROUP BENICH Jum GREEN NEKKEN Order ID: Aailing Address: Attention to: Global ID: Sampler

Ga, Ge, Hg, In, Li, Mo, Ni, P, K, Si, Ag, Na, S, Se, Sr, Ta, Te, Ti, Sn, Ti, Zn, V, W, Zr Metals: See Receipt Log 13:30 Al, As, Sb, Ba, Be, Bi, B, Cd, Ce, Ca, Cr, Co, Cs, Cu, Fe, Pb, Mg, Mn, Metals: ション 7(8/05 Jean Thursh Received by:

□ Plating
 □ LUFT-5
 □ RCRA-8
 □ PPM-13
 □ CAM-17

☐ EDD Report ☐ EDF Report

Use Times listed on bothes per Jonesn

See Perceipt Long

Special Instructions or Comments

CAM-17

elinquished by: